

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	SCHNEIDER RACK PDU, DE BAZA, ZERO U, 11 KW, 230 V, (36) C13 SI (6) C19 Denumire model Rack PDU, de baza, Zero U, 11 kW, 230 V, (36) C13 si (6) C19 Include Ghid de instalare , Console de montare rack , Kit de montare fara scule , Manual de utilizare Timp de livrare standard De obicei in stoc Tensiune nominala la iesire 230V Consum de curent total maxim per faza 16 A Conexiuni de iesire (36) IEC 320 C13 (Battery Backup) , (6) IEC 320 C19 (Battery Backup) Protectie la suprasarcina Nu Tensiune nominala de intrare 400 3 Faz Frecventa de intrare 50/60 Hz Conexiuni de intrare IEC 309 16A 3P+N+PE Lungime cablu 0.91 metri Numar de cabluri de alimentare 1 Curent maxim de intrare per faza 16 A Capacitate sarcina 11000 VA Greutate neta 5.45 kg Inaltime maxima 1778.0 mm Latime maxima 56.0 mm Adancime maxima 44.0 mm Greutate de transport 8.86 kg Inaltime transport 2134.0 mm Latime de transport 152.0 mm Adancime transport 127.0 mm Culoare Negru Mediu de operare -5 - 45 °C Umiditate relativa de functionare 5 - 95 % Inaltime de operare 0-3000 metri Temperatura de depozitare -25 - 65 °C Umiditate relativa depozitare 5 - 95 % Inaltime depozitare 0-15000 metri Aprobari reglementare C-tick , CE , GOST , MIC , Queensland , VDE Garantie standard 2 ani reparatii sau inlocuire RoHS (Restrictionarea substantelor periculoase) Conformitate Alte conformitati cu reglementarile privind protectia mediului RoHS Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/rack-pdu-de-baza-zero-u-11-kw-230-v-36-c13-si-6-c19-101851
---	---