

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>SCHNEIDER RACK PDU, DE BAZA, 1U, 16A, 208 & 230 V, (10) C13 & (2) C19</u> Denumire model Rack PDU, de baza, 1U, 16A, 208 & 230 V, (10) C13 & (2) C19 Include Console de montare rack , Manual de utilizare Timp de livrare standard De obicei in stoc Tensiune nominala la iesire 120V , 208V , 230V Consum de curent total maxim per faza 16 A Conexiuni de iesire (10) IEC 320 C13 (Battery Backup) , (2) IEC 320 C19 (Battery Backup) Protectie la suprasarcina Nu Tensiune nominala de intrare 120V - 208V - 230V Frecventa de intrare 50/60 Hz Conexiuni de intrare IEC-320 C20 Lungime cablu 2.5 metri Numar de cabluri de alimentare 1 Acceptable Input Voltage 90-250 VAC Curent maxim de linie per faza 16 A Curent maxim de intrare per faza 16 A Capacitate sarcina 3680 VA Greutate neta 0.98 kg Inaltime maxima 44.0 mm Latime maxima 447.0 mm Adancime maxima 57.0 mm Greutate de transport 2.36 kg Inaltime transport 165.0 mm Latime de transport 483.0 mm Adancime transport 152.0 mm Culoare Negru Mediu de operare 0 - 45 °C Umiditate relativa de functionare 0 - 95 % Inaltime de operare 0-3000 metri Temperatura de depozitare -25 - 65 °C Umiditate relativa depozitare 0 - 95 % Inaltime depozitare 0-15000 metri Aprobari reglementare CE , Listat UL , VDE , Victo , Listat cUL Garantie standard 2 ani reparatii sau inlocuire RoHS (Restrictionarea substantelor periculoase) Conformitate Alte conformitati cu reglementarile privind protectia mediului RoHS Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/rack-pdu-de-baza-1u-16a-208-230-v-10-c13-2-c19-101856
---	---