


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><u>SCHNEIDER RILUX - VERSIUNE STANDARD - 1 H - 180 LM - NEMENTINUT</u></p> <p>gama Rilux tip produs sau componenta Dispozitiv de iluminat de urgenta domeniul de aplicare al aparatului Iluminare function Standard alimentare Nementinut culoare Alb numar de intrare logica Fluorescent tube 2G7 11 W culoare sursa de lumina Alb tip capac Transparent numar de baterii 1 x 4,8 V 1,5 Ah Ni-Cd (Nickel-Cadmium) informatii suplimentare dispozitiv de conectare Can be inhibited with rest mode via Teleur range of remote controls [Ue] tensiune operationala nominala 200...230 V c.a./c.c. 50 Hz putere consumata 2,9 VA curentul consumat 12 mA clasa de izolatie electrica Clasa II autonomie 1 h ztimp de incarcare 24 H flux luminos Conditia de urgenta 180 lm matel Plastic carcasa - Plastic capac montare dispozitiv Aparent ceiling - Aparent wall - Ingropat inaltime 125 mm latime 280 mm adancime 55 mm greutate produs 0,75 kg segment de piaE>a Cladiri comerciale mici grad de protectie IP IP42 grad de protectie IK IK07 temperatura ambianta pentru utilizare 0...40 °C rezistenta la foc 850 °C standarde IEC 695-2-1 - IEC 50-11 - EN 60695-2-10 - EN 60598-2-22 Stare oferta sustenabila Produs Green Premium Regulamentul REACH Declaratia REACH Directiva RoHS UE Conform Declaratia RoHS UE Fara metale grele toxice Da Fara mercur Da Informatii privind scutirea de la RoHS Da Regulamentul RoHS Declaratia RoHS Declaratia proactiva RoHS (in afara domeniului de aplicare a RoHS) Raport de mediu Profilul ambiental al produsului Profil circularitate Informatii privind sfarsitul duratei de viata Garantie 18 luni Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/rilux-versiune-standard-1-h-180-lm-nementinut-102018</p>
---	---