

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PANOU BYPASS DE INTRETINERE PARALEL APC, PANA
LA 3 UNITATI 10-20 KVA 400 V, MONTAJ IN PERETE**

APC SBPAR10K20H-WP
Denumire model Panou bypass de intretinere paralel APC, pana la 3 unitati 10-20 kVA
400 V, montaj in perete
Include Ghid de instalare , Manual de utilizare
Timp de livrare standard Se livreaza, de regula, in 2 saptamani
,,, Serbia si Muntenegru ,,,,,,,,,,,,,,,,,,,,,, Regatul
Unit ,,
Tensiune nominala la iesire 400 V 3 Faz
Consum de curent total maxim per faza 182.400000 A
Conexiuni de iesire (1) Hard Wire 5-wire (3PH + N + G) (Battery Backup)
Tensiune nominala de intrare 400 V 3 Faz
Frecventa de intrare 50 Hz
Curent maxim de intrare per faza 182.40000000000001 A
Greutate neta 48 kg
Inaltime maxima 1174 mm
Latime maxima 560 mm
Adancime maxima 216 mm
Greutate de transport 53 kg
Inaltime transport 1298 mm
Latime de transport 704 mm
Adancime transport 335 mm
Mediu de operare 0 - 40 °C
Umiditate relativa de functionare 0 - 95 %
Inaltime de operare 0-3000 metri
Temperatura de depozitare -15 - 45 °C
Umiditate relativa depozitare 0 - 95 %
Inaltime depozitare 0-9000 metri
Aprobari reglementare EN 50091-2 , EN/IEC 62040-3 , EN/IEC 62040-1-1 , VFI-SS-111
Garantie standard 1 an reparatii sau inlocuire
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/panou-bypass-de-intretinere-paralel-apc-pana-la-3-unitati-10-20-kva-400-v-montaj-in-perete-102513>