

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER APC PARALLEL MAINTENANCE BYPASS PANEL, UP TO 3 UNITS 30-40KVA, 400V WALLMOUNT

APC SBPAR30K40H-WP

Denumire model APC Parallel Maintenance Bypass Panel, up to 3 units 30-40kVA, 400V Wallmount

Include Installation guide , User Manual

Timp de livrare standard Usually Ships within 2 Weeks

, United Arab Emirates , Afghanistan , , , , Azerbaijan , And Herzegovina , , Belgium , , , , Darussalam , , , , THE DEMOCRATIC REPUBLIC OF THE , Central African Republic , , Switzerland , Cote D'Ivoire , Cook Islands , Cameroon , , Serbia And Montenegro , Cyprus , Czech Republic , Germany , , Denmark , , Egypt , Western Sahara , Spain , Finland , , France , , United Kingdom , , French Guiana , , , Guinea , Guadeloupe , Equatol Guinea , Greece , , Hungary , Indonesia , Ireland , , Iraq , Iran (Islamic Republic Of) , Iceland , Italy , Jordan , Japan , , KOREA, REPUBLIC OF , Kuwait , Cayman Islands , Kazakhstan , Lebanon , , , , Lithuania , Luxembourg , Latvia , Morocco , Moldova, Republic Of , , , Myanmar , Martinique , , , , Malaysia , Mozambique , , , Netherlands , Norway , , New Zealand , , Papua New Guinea , Philippines , , Poland , Portugal , Reunion , , Russian Federation , , Saudi Arabia , , Sweden , , , Slovakia (Slovak Republic) , , , Chad , , Thailand , , , East Timor , Turkey , , TANZANIA, UNITED REPUBLIC OF , Ukraine , , , Viet Nam , , South Africa ,

Tensiune nominala la iesire 400V 3PH

Consum de curent total maxim per faza 182.400000 A

Conexiuni de iesire (1) Hard Wire 5-wire (3PH + N + G) (Battery Backup)

Tensiune nominala de intrare 400V 3PH

Frecventa de intrare 50 Hz

Curent maxim de intrare per faza 182.40000000000001 A

Greutate neta 53 kg

Inaltime maxima 1174 mm

Latime maxima 560 mm

Adancime maxima 216 mm

Greutate de transport 55 kg

Inaltime transport 1298 mm

Latime de transport 704 mm

Adancime transport 335 mm

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 %

Inaltime de operare 0-3000 meters

Temperatura de depozitare -15 - 45 °C

Umiditate relativa depozitare 0 - 95 %

Inaltime depozitare 0-9000 meters

Aprobari reglementare EN 50091-2 , EN/IEC 62040-3 , EN/IEC 62040-1-1 , VFI-SS-111

Garantie standard 1 year repair or replace

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/apc-parallel-maintenance-bypass-panel-up-to-3-units-30-40kva-400v-wallmount-102514>