

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 1-CONDUCTOR FEMALE PLUG; 2.5 MM<sup>2</sup>; 5-POLE; 2,50 MM<sup>2</sup>;  
GRAY, BLUE, GREEN-YELLOW**

Ratings per: IEC/EN 61984;  
Tensiune nominala (III/3): 690; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 20; A  
Curent nominal 2: 32; A  
Tensiune nominala EN (Ex e II): 630; V  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Open Tool Slot; Push-in;  
Connectable conductor materials: Copper;  
Nominal cross-section: 2.5 mm<sup>2</sup>;  
Solid conductor: 0.25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Solid conductor; push-in termination: 0.75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor: 0.25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 1 ... 2.5 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2.5 mm<sup>2</sup> / 18 ... 12 AWG;  
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;  
Numar poli: 5;  
Numar total de conexiuni: 5;  
Total number of potentials: 5;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;  
Latime: 26 mm / 1.024 inch;  
Inaltime: 40.5 mm / 1.594 inch;  
Adancime: 22.4 mm / 0.882 inch;  
Module Latime: 5.2 mm / 0.205 inch;  
Marking level: Side marking;  
Tip contact (pluggable connector): Conector mama/priza;  
Connector (connection type): for conductors;  
Culoare: gray, blue, green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 16,5; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143535670;  
Customs tariff number: 85366990990;  
Pret: 39,15 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-plug-2-5-mm2-5-pole-2-50-mm2-gray-blue-green-yellow-148839>