


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHRACK Technik GmbH, AT-1220 Wien, Spitzgasse 13, Phone: +43 1 86685-0, www.schrack.com

SCHRACK COMBINED MCB/RCD (RCBO) C25/1+N/30mA/TYPE A, G

EAN-Code 9004840105155 Latime neta 35,60mm Inaltime 80,00mm Adancime neta 70,00mm Masa neta 0,22kg. disipare 4,80W Temperatura minima a mediului ambiant -35°C Temperatura maxima a mediului ambiant 60°C Caracteristica declansare C Curent nominal 25A Poli 1+N Valoare curent de defect 30mA Tip temporizat Categorie produs A (sensibil la curent alternativ si pulsatoriu) Serie BOLF Capacitate de rupere nominala 10kA Standard produs EN 61009
Pret: 742,23 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/combined-mcb-rcd-rcbo-c25-1-n-30ma-type-a-g-119372>