

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

 <p>The diagram shows a three-phase power supply (LINE) with phases L1, L2, and L3. The power is connected to a thermal relay (T1, T2, T3) and a contactor (C1, C2, C3). The contactor is controlled by a start button (I) and a stop button (O). The thermal relay is connected to the motor windings (A1, A2) and a load. The voltage coil contactor (C4) is connected to the motor windings and a load. The diagram also shows a legend: I = Start, O = Stop, E = Emergency Stop.</p>	<p><u>LOVATO DEMAROR PORNIRE DIRECTA, IN CARCASA CU INTRERUPATOR PROTECTIE MOTOR, 2.5A (440V), IP65. CONTACTOR BOBINA TENSIUNE 460VAC 60HZ</u></p> <p>Limitator de cursa, K SERIES, ROLLER SIDE PUSH LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 2NO SLOW BREAK. METAL ROLLER</p> <p>Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/demaror-pornire-directa-in-carcasa-cu-intrerupator-protectie-motor-2-5a-440v-ip65-contactor-bobina-tensiune-460vac-60hz-123000</p>
---	--