

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO PCB TERMINAL BLOCK; 2.5 MM<sup>2</sup>; PIN SPACING 5/5.08 MM; 9-POLE; CAGE CLAMP®; COMMONING OPTION; 2,50 MM<sup>2</sup>; GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;                  Tensiune nominala (III/3): 250; V                  Tensiune nominala de supratensiune (III/3): 4; kV                  Tensiune nominala (III/2): 320; V                  Tensiune nominala de supratensiune (III/2): 4; kV                  Tensiune nominala (II/2): 630; V                  Tensiune nominala de supratensiune (II/2): 4; kV                  Curent nominal: 24; A                  Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2;                  Tensiune nominala UL (Use Group B): 300; V                  Curent nominal UL (Use Group B): 15; A                  Tensiune nominala UL (Use Group D): 300; V                  Curent nominal UL (Use Group D): 10; A                  Certificari: UL 1059;                  Tensiune nominala CSA (Use Group B): 300; V                  Curent nominal CSA (Use Group B): 15; A                  Tensiune nominala CSA (Use Group D): 300; V                  Curent nominal CSA (Use Group D): 10; A                  Tehnologie conexiune: CAGE CLAMP®;                  Tip actionare: Operating tool;                  Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;                  Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;                  Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;                  Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;                  Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;                  Conductor connection direction to PCB: 45; °                  Numar poli: 9;                  Numar total de conexiuni: 9;                  Total number of potentials: 9;                  Numar tipuri de conexiuni: 1;                  Numar nivele: 1;                  Note (conductor cross-section): 12 AWG: THHN, THWN;                  Distanta intre pini: 5/5.08 mm / 0.197/0.2 inch;                  Latime: 47.3 mm / 1.862 inch;                  Inaltime: 17 mm / 0.669 inch;                  Inaltime de la fata: 13 mm / 0.512 inch;                  Adancime: 14 mm / 0.551 inch;                  Lungimea pinului de contact: 4; mm                  Solder pin dimensions: 0.7 x 0.7 mm;                  Diametrul de gaurire cu toleranta: 1.1 (+0.1) mm;                  PCB contact: THT;                  Solder pin arrangement: over the entire terminal strip, in line;                  Number of solder pins per potential: 1;                  Culoare: gray;                  Material group: I;                  Material izolator: Polyamide 66 (PA 66);                  Flammability class per UL94: V0;                  Clamping spring material: Chrome nickel spring steel (CrNi);                  Contact material: Cupru electrolitic(ECu);                  Contact plating: tin-plated;                  Fire load: 0,112; MJ                  Greutate: 7,8; g                  Temperatura lucru: -60 ... +105 °C;                  Product Group: 4 (Printed Circuit);                  Tip ambalare: BOX;                  Tara de origine: CH;                  GTIN: 4044918766548;                  Customs tariff number: 85369010000;                  Pret: 12,84 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/pcb-terminal-block-2-5-mm2-pin-spacing-5-5-08-mm-9-pole-cage-clamp-commoning-option-2-50-mm2-gray-130393">https://www.materialelectrice.ro/pcb-terminal-block-2-5-mm2-pin-spacing-5-5-08-mm-9-pole-cage-clamp-commoning-option-2-50-mm2-gray-130393</a></p>
--	--