

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

| | |
|--|---|
| <p>Technical drawings of the WAGO THR Male Header showing top, side, and cross-sectional views with dimensions:</p> <ul style="list-style-type: none"> Top view: Overall length L, pin spacing 5 mm, pin diameter 1.4 mm, contact diameter 2.4 mm, mounting hole diameter 1.6 mm (+0.1 mm). Side view: Overall height 19.5 mm, mounting hole diameter 3.6 mm, PCB contact height 14.4 mm. Cross-sectional view: Pin diameter 1.4 mm, contact diameter 2.4 mm, PCB contact height 18.6 mm, overall height 17.9 mm. | <p>WAGO THR MALE HEADER; 1.4 MM Ø ~ SOLDER PIN; STRAIGHT; PIN SPACING 5 MM; 2-POLE; LIGHT GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Numar poli: 2; Total number of potentials: 2; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 5 mm / 0.197 inch; Latime: 12,2 mm / 0.48 inch; Inaltime: 21,9 mm / 0.862 inch; Inaltime de la fata: 19,5 mm / 0.768 inch; Adancime: 14,4 mm / 0.567 inch; Lungimea pinului de contact: 2,4; mm Diametrul pinului de contact: 1,4; mm Diametru placat prin gaura (THR): 1,6 (+0,1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCB; Mismatching protection: No; Mating direction to the PCB: 90; ° Locking of plug-in connection: Locking latch; PCB contact: THR; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,036; MJ Greutate: 1,6; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821395638; Customs tariff number: 85366990990; Pret: 2,57 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-straight-pin-spacing-5-mm-2-pole-light-gray-130962</p> |
|--|---|