

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410




Plate thickness: 0.5 ... 2 mm
Cutout tolerance: + 0.1 mm

**WAGO SNAP-IN SOCKET; WITHOUT LOCKING LEVER; 2-POLE; COD.
F; LIGHT GRAY**

Note on Contact Resistance: \approx approx. 3m Ω , contact resistance
Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 50; V
Tensiune nominala de supratensiune (III/3): 0,8; kV
Curent nominal: 3; A
Legend (ratings): (III / 3) $\hat{=}$ Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Conductor diameter: 0,8 mm;
Strip length: 9 mm / 0.35 inch;
Note (strip length): see also packaging or instructions;
Numar poli: 2;
Numar total de conexiuni: 2;
Total number of potentials: 2;
Conductor entry direction to mating direction: 0; °
Latime: 19,6 mm / 0.772 inch;
Inaltime: 19,6 mm / 0.772 inch;
Adancime: 29,5 mm / 1.161 inch;
Tehnologie: KNX;
Coding: F;
Mating force of a plug-in connection: approx. 10 ... 15 N;
Retention force of a plug-in connection: Locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;
Number of mating cycles: \approx 200;
Housing sheet thickness: 0,5 ... 2 mm / 0.02 ... 0.079 inch;
Tip montaj: Snap-in;
Marking: 1+ 2-;
Protection type: IP20;
Note on protection type: Only when mated and secured with a strain relief housing
(These compact connectors are not designed for use in open, easily accessible areas.);
Potential marking: 1+ 2-;
Application: KNX;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductor;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy (surface-treated);
Greutate: 4,5; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures \leq 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454420161;
Customs tariff number: 85366990990;
Pret: 36,97 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/snap-in-socket-without-locking-lever-2-pole-cod-f-light-gray-131099>