


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO THR MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN;
 STRAIGHT; 100% PROTECTED AGAINST MISMATING; IN TAPE-AND-
 REEL PACKAGING; PIN SPACING 3.5 MM; 2 X 6-POLE; BLACK**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 80; V
 Tensiune nominala de supratensiune (III/3): 2,5; kV
 Tensiune nominala (III/2): 160; V
 Tensiune nominala de supratensiune (III/2): 2,5; kV
 Tensiune nominala (II/2): 250; V
 Tensiune nominala de supratensiune (II/2): 2,5; kV
 Curent nominal: 10; A
 Legend (ratings): (III / 2) $\hat{a}\%$ ™ Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 150; V
 Curent nominal UL (Use Group B): 10; A
 Tensiune nominala UL (Use Group C): 50; V
 Curent nominal UL (Use Group C): 10; A
 Certificari: UL 1059;
 Tensiune nominala CSA (Use Group B): 150; V
 Curent nominal CSA (Use Group B): 12; A
 Numar poli: 12;
 Total number of potentials: 12;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 2;
 Distanta intre pini: 3,5 mm / 0.138 inch;
 Latime: 22,5 mm / 0.886 inch;
 Inaltime: 15,9 mm / 0.626 inch;
 Inaltime de la fata: 13,5 mm / 0.531 inch;
 Adancime: 13,3 mm / 0.524 inch;
 Lungimea pinului de contact: 2,4; mm
 Solder pin dimensions: 0,8 x 0,8 mm;
 Diametru placat prin gaura (THR): 1,3 (+0,1) mm;
 Reel diameter of tape-and-reel packaging: 330; mm
 Tape Latime: 44; mm
 Tip contact (pluggable connector): Conector tata/fisa;
 Connector (connection type): for PCB;
 Mismatching protection: Yes;
 Mating direction to the PCB: 90; °
 PCB contact: THR;
 Solder pin arrangement: over the entire male connector (in-line);
 Number of solder pins per potential: 1;
 Culoare: black;
 Material group: I;
 Material izolator: Polyphthalamide (PPA GF);
 Flammability class per UL94: V0;
 Contact material: Cupru electrolitic(ECu);
 Contact plating: tin-plated;
 Fire load: 0,075; MJ
 Greutate: 3,2; g
 Temperatura lucru: -60 ... +100 °C;
 Tip ambalare: bag;
 Tara de origine: DE;
 GTIN: 4050821308577;
 Customs tariff number: 85366990990;
 Pret: 18,69 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/thr-male-header-2-row-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismatching-in-tape-and-reel-packaging-pin-spacing-3-5-mm-2-x-6-pole-black-131400>