

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p><u>WAGO 3-CONDUCTOR ACTUATOR SUPPLY TERMINAL BLOCK; LED (YELLOW); FOR NPN-(LOW-SIDE) SWITCHING ACTUATORS; WITH GROUND CONNECTION VIA PUSH-IN TYPE JUMPER BARS; 1 MM²; PUSH-IN CAGE CLAMP®; 1,00 MM²; GRAY</u></p> <p>Voltage type 1: DC; Tensiune nominala: 24; V Ratings per: IEC/EN 60947-7-1; Curent nominal: 13,5; A Tensiune nominala UL (Use Group C): 24; V Curent nominal UL (Use Group C): 15; A Certificari: UL 1059; Tensiune nominala CSA (Use Group C): 24; V Curent nominal CSA (Use Group C): 10; A Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-in; Open Tool Slot; Connectable conductor materials: Copper; Nominal cross-section: 1 mm²; Solid conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG; Solid conductor; push-in termination: 0,5 ... 1,5 mm² / 20 ... 16 AWG; Fine-stranded conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG; Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm² / 20 ... 18 AWG; Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm² / 20 ... 18 AWG; Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch; Numar total de conexiuni: 8; Total number of potentials: 4; Numar nivele: 1; Wiring type: Front-entry wiring; Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.; Latime: 7 mm / 0.276 inch; Inaltime from upper-edge of DIN-rail: 52,4 mm / 2.063 inch; Adancime: 81,1 mm / 3.193 inch; Design: horizontal type; Tip montaj: DIN-35 rail; Marking level: Center/side marking; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Greutate: 16,8; g Tip ambalare: BOX; Tara de origine: DE; GTIN: 4055143452922; Customs tariff number: 85369010000; Pret: 73,19 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectriche.ro/3-conductor-actuator-supply-terminal-block-led-yellow-for-npn-low-side-switching-actuators-with-ground-connection-via-push-in-type-jumper-bars-1-mm2-push-in-cage-clamp-1-00-mm2-gray-131501</p>
--	---