

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 6 MM<sup>2</sup>; WITH TOUCH-PROOF TEST SOCKET; FOR 4 MM  $\tilde{A}$  TEST PLUGS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 6,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 30; A  
Legend (ratings): (III / 3)  $\hat{A}$ %™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL (Use Group B): 300; V  
Curent nominal UL (Use Group B): 30; A  
Tensiune nominala UL (Use Group C): 300; V  
Curent nominal UL (Use Group C): 30; A  
Tensiune nominala UL (Use Group D): 300; V  
Curent nominal UL (Use Group D): 10; A  
Certificari: UL 1059;  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Push-in; Open Tool Slot;  
Connectable conductor materials: Copper;  
Nominal cross-section: 6 mm<sup>2</sup>;  
Solid conductor: 0,5 ... 10 mm<sup>2</sup> / 20 ... 8 AWG;  
Solid conductor; push-in termination: 1 ... 10 mm<sup>2</sup> / 14 ... 8 AWG;  
Fine-stranded conductor: 0,5 ... 10 mm<sup>2</sup> / 20 ... 8 AWG;  
Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm<sup>2</sup> / 16 ... 10 AWG;  
Fine-stranded conductor; with uninsulated ferrule: 1,5 ... 6 mm<sup>2</sup> / 16 ... 10 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm<sup>2</sup> / 16 ... 16 AWG;  
Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;  
Numar total de conexiuni: 2;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Number of jumper slots: 2;  
Latime: 8 mm / 0.315 inch;  
Inaltime from upper-edge of DIN-rail: 46,8 mm / 1.843 inch;  
Adancime: 99,6 mm / 3.921 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 22; g  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4055143394840;  
Customs tariff number: 85369010000;  
Pret: 34,57 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-6-mm2-with-touch-proof-test-socket-for-4-mm-oe-test-plugs-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-6-00-mm2-gray-131748>