


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO 3-CONDUCTOR SENSOR/ACTUATOR TERMINAL BLOCK; FOR NPN-(LOW-SIDE) SWITCHING ACTUATORS; WITH GROUND CONTACT; WITH COLORED CONDUCTOR ENTRIES; 2.5 MM²; PUSH-IN CAGE CLAMP[®]; 2,50 MM²; ORANGE

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 250; V
Curent nominal: 28; A
Legend (ratings): (III / 3) %[™] Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 20; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group C): 300; V
Curent nominal CSA (Use Group C): 20; A
Tehnologie conexiune: Push-in CAGE CLAMP[®];
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 1 mm²;
Solid conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG;
Solid conductor; push-in termination: 0,5 ... 1,5 mm² / 20 ... 16 AWG;
Fine-stranded conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm² / 20 ... 18 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm² / 20 ... 18 AWG;
Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;
Solid conductor 2: 0,25 ... 4 mm² / 22 ... 12 AWG;
Solid conductor, push-in termination 2: 0,25 ... 4 mm² / 22 ... 12 AWG;
Fine-stranded conductor 2: 0,25 ... 4 mm² / 22 ... 12 AWG;
Numar total de conexiuni: 8;
Total number of potentials: 2;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Latime: 7 mm / 0.276 inch;
Inaltime from upper-edge of DIN-rail: 52,4 mm / 2.063 inch;
Adancime: 81,1 mm / 3.193 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: orange;
Material izolator: Polyamide 66 (PA 66);
Greutate: 17,9; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143497107;
Customs tariff number: 85369010000;
Pret: 53,55 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-sensor-actuator-terminal-block-for-npn-low-side-switching-actuators-with-ground-contact-with-colored-conductor-entries-2-5-mm2-push-in-cage-clamp-2-50-mm2-orange-131754>