

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO PRE-ASSEMBLED CONNECTING CABLE; CCA; SOCKET/OPEN-ENDED; 5-POLE; COD. I; H05Z1Z1-F 5G 1.5 MM<sup>2</sup>; 1 M; 1,50 MM<sup>2</sup>; BLUE**

Note on Contact Resistance: approx. 1 m $\Omega$ ; of contact resistance $\hat{c}$  approx. 0.25 m $\Omega$ ;  
contact transition plug/socket;  
Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 400; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 16; A  
Legend (ratings): (III / 3)  $\hat{c}$ ™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL 1977: 600; V  
Curent nominal UL 1977: 23; A  
Strip length: 9 mm / 0.35 inch;  
Numar poli: 5;  
Total number of potentials: 5;  
Conductor preparation: tip-bonded;  
Sheathed cable diameter: 9,3 ... 11,6 mm;  
Sectiunea transversala a firului: 1,5; mm<sup>2</sup>  
Strip length (outer insulation): 55; mm  
Connection type: Socket - Free end;  
Distanța intre pini: 10 mm / 0.394 inch;  
Total length: 1; m  
Technologie: DALI;  
Coding: I;  
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);  
Retention force of a plug-in connection: when locked: > 80N;  
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);  
Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm<sup>2</sup>);  
Connection type: Socket - Free end;  
Type of pre-assembled cable: Connecting cable;  
Cable type: H05Z1Z1-F 5G1.5;  
Marking: N  $\hat{c}$  L DA- DA+;  
Protection type: IP20;  
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;  
Potential marking: N  $\hat{c}$  L DA- DA+;  
Application: Lighting management;  
Mismating protection: Yes;  
Locking of plug-in connection: locking lever;  
Locking lever: retrofittable;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Fire class per EN 50575: Cca;  
Contact material: Copper or copper alloy (surface-treated);  
Connector Culoare: blue;  
Printing color of mating face: white;  
Strain relief Culoare: black;  
Printing color of strain relief: white;  
Sheathed cable Culoare: black;  
Printing color of sheathed cable: white;  
Halogen-free: Yes;  
Greutate: 179; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: PVC cable for temperatures  $\leq$  70 °C (including halogen-free) Insulating parts for temperatures  $\leq$  105 °C;  
Tip ambalare: not packed;  
Tara de origine: DE;  
GTIN: 4055143841672;  
Customs tariff number: 85444290900;  
Pret: 85,79 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-connecting-cable-cca-socket-open-ended-5-pole-cod-i-h05z1z1-f-5g-1-5-mm2-1-m-1-50-mm2-blue-131853>