

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

<p>Technical drawing of a WAGO THT Female Header. The drawing includes three views: a top view showing the four poles with dimensions 2.6, 3.4, 2.2, L1, L2, L3, and 2; a side view showing the height of the header with dimensions 11.6, 18.25, 9.8, and 4.4; and a detail view of the contact area with dimensions 5.1, 2.6, 5, 3.4, 7, and 4.9.</p>	<p><b>WAGO THT FEMALE HEADER; 0.6 X 1.0 MM SOLDER PIN; ANGLED; SPACER FLANGE; PIN SPACING 5 MM; 4-POLE; GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;          Tensiune nominala (III/3): 320; V          Tensiune nominala de supratensiune (III/3): 4; kV          Tensiune nominala (III/2): 320; V          Tensiune nominala de supratensiune (III/2): 4; kV          Tensiune nominala (II/2): 630; V          Tensiune nominala de supratensiune (II/2): 4; kV          Curent nominal: 12; A          Legend (ratings): (III / 2) <math>\hat{a}</math>%<sup>TM</sup> Overvoltage category III / Pollution degree 2;          Tensiune nominala UL (Use Group B): 300; V          Curent nominal UL (Use Group B): 15; A          Tensiune nominala UL (Use Group D): 300; V          Curent nominal UL (Use Group D): 10; A          Certificari: UL 1059;          Tensiune nominala UL 1977: 600; V          Curent nominal UL 1977: 15; A          Tensiune nominala CSA (Use Group B): 300; V          Curent nominal CSA (Use Group B): 15; A          Tensiune nominala CSA (Use Group D): 300; V          Curent nominal CSA (Use Group D): 10; A          Numar poli: 4;          Total number of potentials: 4;          Numar tipuri de conexiuni: 1;          Numar nivele: 1;          Distanta intre pini: 5 mm / 0.197 inch;          Latime: 34.8 mm / 1.37 inch;          Inaltime: 16.6 mm / 0.654 inch;          Inaltime de la fata: 11.6 mm / 0.457 inch;          Adancime: 18.25 mm / 0.719 inch;          Lungimea pinului de contact: 5; mm          Solder pin dimensions: 0.6 x 1 mm;          Diametrul de gaurire cu toleranta: 1.3 (+0.1) mm;          Tip montaj: Mounting flange;          Tip montaj: Flush mounting; Panel mounting;          Tip contact (pluggable connector): Conector mama/priza;          Connector (connection type): for PCBs;          Mismatching protection: No;          Mating direction to the PCB: 0; °          PCB contact: THT;          Solder pin arrangement: over the entire female connector, in line;          Number of solder pins per potential: 1;          Culoare: gray;          Material group: I;          Material izolator: Polyamide 66 (PA 66);          Flammability class per UL94: V0;          Contact material: Copper alloy;          Contact plating: tin-plated;          Fire load: 0,093; MJ          Greutate: 4,7; g          Temperatura lucru: -60 ... +85 °C;          Product Group: 3 (Multi Conn. System);          Tip ambalare: BOX;          Tara de origine: DE;          GTIN: 4044918624657;          Customs tariff number: 85366990990;          Pret: 12,78 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-angled-spacer-flange-pin-spacing-5-mm-4-pole-gray-131865">https://www.materialeelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-angled-spacer-flange-pin-spacing-5-mm-4-pole-gray-131865</a></p>
---	--