

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



Image coming soon

**WAGO 2-CONDUCTOR TERMINAL STRIP; 4-POLE; ON ONE SIDE
WITH PUSH-BUTTONS; WITH FIXING FLANGES; FOR SCREW OR
SIMILAR MOUNTING TYPES; FIXING HOLE 3.2 MM Å; 2.5 MMÅ²;
CAGE CLAMPÅ; 2,50 MMÅ²; GRAY**

Tensiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 24; A
Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMPÅ;
Tip actionare: Operating tool; Push-button;
Connectable conductor materials: Copper;
Solid conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;
Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 4;
Numar total de conexiuni: 8;
Total number of potentials: 4;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 38.5 mm / 1.516 inch;
Inaltime de la fata: 23.2 mm / 0.913 inch;
Adancime: 28 mm / 1.102 inch;
Module Latime: 6 mm / 0.236 inch;
Design: horizontal;
Tip montaj: Mounting flange;
Marking level: Side marking;
Culoare: gray;
Fire load: 0,217; MJ
Greutate: 10,9; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918617215;
Customs tariff number: 85369010000;
Pret: 11,47 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-terminal-strip-4-pole-on-one-side-with-push-buttons-with-fixing-flanges-for-screw-or-similar-mounting-types-fixing-hole-3-2-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-gray-131916>