

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO 1-CONDUCTOR THT FEMALE HEADER; 1.0 MM Å~ SOLDER PIN; ANGLED; GRIPPING PLATE; 1.5 MMÅ²; PIN SPACING 3.5 MM; 8- POLE; 1.50 MMÅ²; LIGHT GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 160; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) â‰‰™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-button; Solid conductor: 0,2 ... 1,5 mm² / 24 ... 14 AWG; Fine-stranded conductor: 0,2 ... 1,5 mm² / 24 ... 14 AWG; Fine-stranded conductor; with insulated ferrule: 0,25 ... 0,75 mm²; Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1,5 mm²; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Conductor connection direction to PCB: 0; ° Numar poli: 8; Numar total de conexiuni: 8; Total number of potentials: 8; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanța între pini: 3,5 mm / 0.138 inch; Latime: 28 mm / 1.102 inch; Inaltime: 11,4 mm / 0.449 inch; Adancime: 33 mm / 1.299 inch; Lungimea pinului de contact: 3,6; mm Diametrul pinului de contact: 1; mm Diametrul de gaurire cu toleranta: 1,2 (+0,1) mm; Design: With gripping plate; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for PCB; Mismating protection: No; Mating direction to the PCB: 0; ° PCB contact: THT; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ESu); Contact plating: tin-plated; Fire load: 0,097; MJ Greutate: 4,8; g Temperatura lucru: -60 ... +100 °C; Product Group: 26 (picoMAX); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821162834; Customs tariff number: 85366990990; Pret: 27,46 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/1-conductor-tht-female-header-1-0-mm-oe-solder-pin-angled-gripping-plate-1-5-mm2-pin-spacing-3-5-mm-8-pole-1-50-mm2-light-gray-131986</p>
--	---