


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO DOUBLE POTENTIAL TERMINAL BLOCK; 1.5 MM<sup>2</sup>; SUITABLE FOR EX E II APPLICATIONS; LATERAL MARKER SLOTS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 1.50 MM<sup>2</sup>; LIGHT GRAY**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala EN (Ex e II): 550; V  
Curent nominal (Ex e II): 15; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;  
Fine-stranded conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 2;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 4 mm / 0.157 inch;  
Inaltime from upper-edge of DIN-rail: 27 mm / 1.063 inch;  
Adancime: 68 mm / 2.677 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Side marking;  
Culoare: light gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,103; MJ  
Greutate: 5,6; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918506540;  
Customs tariff number: 85369010000;  
Pret: 10,62 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-potential-terminal-block-1-5-mm2-suitable-for-ex-e-ii-applications-lateral-marker-slots-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-1-50-mm2-light-gray-132106>