

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO PCB TERMINAL BLOCK; LEVER; 4 MM²; PIN SPACING 11.5 MM; 12-POLE; PUSH-IN CAGE CLAMP®; 4.00 MM²; GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 1000; V Tensiune nominala de supratensiune (III/3): 8; kV Tensiune nominala (III/2): 1000; V Tensiune nominala de supratensiune (III/2): 8; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 8; kV Curent nominal: 32; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 600; V Curent nominal UL (Use Group B): 20; A Tensiune nominala UL (Use Group C): 600; V Curent nominal UL (Use Group C): 20; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Lever; Solid conductor: 0,2 ... 4 mm² / 24 ... 12 AWG; Fine-stranded conductor: 0,2 ... 4 mm² / 24 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0,25 ... 2,5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²; Fine-stranded conductor; with twin ferrule: 0,25 ... 1,5 mm²; Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch; Conductor connection direction to PCB: 90; ° Numar poli: 12; Numar total de conexiuni: 12; Total number of potentials: 12; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 11,5 mm / 0.453 inch; Latime: 133,9 mm / 5.272 inch; Inaltime: 25,3 mm / 0.996 inch; Inaltime de la fata: 21,3 mm / 0.839 inch; Adancime: 16,7 mm / 0.657 inch; Lungimea pinului de contact: 4; mm Solder pin dimensions: 0,8 x 1 mm; Diametrul de gaurire cu toleranta: 1,3 (+0,1) mm; PCB contact: THT; Solder pin arrangement: over the entire terminal strip (in-line); Number of solder pins per potential: 2; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Color of actuator: orange; Greutate: 31,9; g Temperatura lucru: -60 ... +105 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4055143565080; Customs tariff number: 85369010000; Pret: 64,60 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/pcb-terminal-block-lever-4-mm2-pin-spacing-11-5-mm-12-pole-push-in-cage-clamp-4-00-mm2-gray-132134</p>
--	---