


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO SPARE SUPPLY TERMINAL BLOCK; 16 MM<sup>2</sup>; 12 MM; PUSH-IN  
CAGE CLAMP®; 16,00 MM<sup>2</sup>; GRAY**

Tesiune nominala (III/3): 800; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 76; A  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Push-in; Open Tool Slot;  
Connectable conductor materials: Copper;  
Nominal cross-section: 16 mm<sup>2</sup>;  
Solid conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;  
Solid conductor; push-in termination: 6 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;  
Fine-stranded conductor: 0,5 ... 25 mm<sup>2</sup> / 20 ... 4 AWG;  
Fine-stranded conductor; with insulated ferrule: 6 ... 16 mm<sup>2</sup> / 10 ... 6 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 6 ... 16 mm<sup>2</sup> / 10 ... 6 AWG;  
Strip length: 18 ... 20 mm / 0.71 ... 0.79 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;  
Number of jumper slots: 2;  
Latime: 12 mm / 0.472 inch;  
Inaltime from upper-edge of DIN-rail: 40,8 mm / 1.606 inch;  
Adancime: 85,7 mm / 3.374 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 43,6; g  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4055143622820;  
Customs tariff number: 85369010000;  
Pret: 33,74 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/spare-supply-terminal-block-16-mm2-12-mm-push-in-cage-clamp-16-00-mm2-gray-132161>