


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b><u>WAGO DOUBLE-DECK TERMINAL BLOCK; THROUGH/THROUGH TERMINAL BLOCK; WITH END PLATE; N/N; WITH MARKER CARRIER; SUITABLE FOR EX I APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 1 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 1,00 MM<sup>2</sup>; BLUE</u></b></p> <p>Ratings per: IEC/EN 60947-7-1; Tesiune nominala (III/3): 800; V Tensiune nominala de supratensiune (III/3): 8; kV Curent nominal: 13,5; A Curent nominal 2: 16; A Legend (ratings): (III / 3) %<sup>o</sup>™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL (Use Group B): 600; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group C): 600; V Curent nominal UL (Use Group C): 15; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-in; Open Tool Slot; Connectable conductor materials: Copper; Nominal cross-section: 1 mm<sup>2</sup>; Solid conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG; Solid conductor; push-in termination: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 16 AWG; Fine-stranded conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG; Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG; Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG; Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch; Numar total de conexiuni: 4; Total number of potentials: 2; Numar nivele: 2; Wiring type: Front-entry wiring; Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.; Latime: 4,2 mm / 0.165 inch; Inaltime from upper-edge of DIN-rail: 61,8 mm / 2.433 inch; Adancime: 69,7 mm / 2.744 inch; Design: horizontal type; Tip montaj: DIN-35 rail; Potential marking: N/N; Marking level: Center/side marking; Culoare: blue; Material izolator: Polyamide 66 (PA 66); Fire load: 0,226; MJ Greutate: 9,8; g Product Group: 22 (TOPJOB S); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821037682; Customs tariff number: 85369010000; Pret: 14,61 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/double-deck-terminal-block-through-through-terminal-block-with-end-plate-n-n-with-marker-carrier-suitable-for-ex-i-applications-for-din-rail-35-x-15-and-35-x-7-5-1-mm2-push-in-cage-clamp-1-00-mm2-blue-132301">https://www.materialelectrice.ro/double-deck-terminal-block-through-through-terminal-block-with-end-plate-n-n-with-marker-carrier-suitable-for-ex-i-applications-for-din-rail-35-x-15-and-35-x-7-5-1-mm2-push-in-cage-clamp-1-00-mm2-blue-132301</a></p>
---	---