

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO PCB TERMINAL BLOCK; 2.5 MM<sup>2</sup>; PIN SPACING 5/5.08 MM; 7-POLE; PUSH WIRE<sup>®</sup>; 2,50 MM<sup>2</sup>; GRAY</b></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 320; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 24; A Legend (ratings): (III / 2) <sup>â%</sup>™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: PUSH WIRE<sup>®</sup>; Tip actionare: Operating tool; Solid conductor: 0.5 ... 2.5 mm<sup>2</sup> / 20 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0.5 ... 1.5 mm<sup>2</sup>; Fine-stranded conductor; with uninsulated ferrule: 0.5 ... 1.5 mm<sup>2</sup>; Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch; Conductor connection direction to PCB: 45; ° Numar poli: 7; Numar total de conexiuni: 7; Total number of potentials: 7; Numar tipuri de conexiuni: 1; Numar nivele: 1; Note (conductor cross-section): 12 AWG: THHN, THWN; Distanța între pini: 5/5.08 mm / 0.197/0.2 inch; Latime: 36.5 mm / 1.437 inch; Inaltime: 19.7 mm / 0.776 inch; Inaltime de la fata: 15.7 mm / 0.618 inch; Adancime: 13.5 mm / 0.531 inch; Lungimea pinului de contact: 4; mm Solder pin dimensions: 0.5 x 0.75 mm; Diametrul de gaurire cu toleranta: 1.1 (+0.1) mm; PCB contact: THT; Solder pin arrangement: over the entire terminal strip, in line; Number of solder pins per potential: 2; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,132; MJ Greutate: 7,5; g Temperatura lucru: -60 ... +105 °C; Product Group: 4 (Printed Circuit); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4044918940658; Customs tariff number: 85369010000; Pret: 10,63 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/pcb-terminal-block-2-5-mm2-pin-spacing-5-5-08-mm-7-pole-push-wire-2-50-mm2-gray-132730">https://www.materialelectrice.ro/pcb-terminal-block-2-5-mm2-pin-spacing-5-5-08-mm-7-pole-push-wire-2-50-mm2-gray-132730</a></p>
--	---