


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO 1-CONDUCTOR FEMALE CONNECTOR, 2-ROW; 100%
 PROTECTED AGAINST MISMATING; DIRECT MARKING; 1.5 MM²;
 PIN SPACING 3.5 MM; 24-POLE; 1.50 MM²; BLACK**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 80; V
 Tensiune nominala de supratensiune (III/3): 2,5; kV
 Tensiune nominala (III/2): 160; V
 Tensiune nominala de supratensiune (III/2): 2,5; kV
 Tensiune nominala (II/2): 250; V
 Tensiune nominala de supratensiune (II/2): 2,5; kV
 Curent nominal: 10; A
 Legend (ratings): (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 300; V
 Curent nominal UL (Use Group B): 10; A
 Tensiune nominala UL (Use Group C): 50; V
 Curent nominal UL (Use Group C): 10; A
 Certificari: UL 1059;
 Tensiune nominala CSA (Use Group B): 300; V
 Curent nominal CSA (Use Group B): 10; A
 Tehnologie conexiune: CAGE CLAMP®;
 Tip actionare: Operating tool;
 Solid conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;
 Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 1 mm²;
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1 mm²;
 Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;
 Numar poli: 24;
 Numar total de conexiuni: 24;
 Total number of potentials: 24;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 2;
 Conductor entry direction to mating direction: 0; °
 Distanta intre pini: 3,5 mm / 0.138 inch;
 Latime: 43,5 mm / 1.713 inch;
 Inaltime: 18,8 mm / 0.74 inch;
 Adancime: 16 mm / 0.63 inch;
 Tip contact (pluggable connector): Conector mama/priza;
 Connector (connection type): for conductor;
 Mismatching protection: Yes;
 Culoare: black;
 Material group: II;
 Material izolator: Glass fiber-reinforced polyamide (PA°66°GF);
 Flammability class per UL94: V0;
 Clamping spring material: Chrome nickel spring steel (CrNi);
 Contact material: Copper alloy;
 Contact plating: tin-plated;
 Fire load: 0,179; MJ
 Greutate: 12,2; g
 Temperatura lucru: -60 ... +100 °C;
 Product Group: 3 (Multi Conn. System);
 Tip ambalare: BOX;
 Tara de origine: PL;
 GTIN: 4050821176510;
 Customs tariff number: 85366990990;
 Pret: 92,63 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-connector-2-row-100-protected-against-mismatching-direct-marking-1-5-mm2-pin-spacing-3-5-mm-24-pole-1-50-mm2-black-132798>