

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO PRE-ASSEMBLED CONNECTING CABLE; SOCKET/OPEN-ENDED; 2-POLE; COD. F; 1 M; GRAY</u> Note on Contact Resistance: $i \geq p$ approx. 3mΩ, contact resistance Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 50; V Tensiune nominala de supratensiune (III/3): 0,8; kV Curent nominal: 3; A Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3; Conductor diameter: 0,8 mm; Strip length: 9 mm / 0.35 inch; Numar poli: 2; Total number of potentials: 2; Conductor preparation: tip-bonded; Strip length (outer insulation): 23; mm Connection type: Socket - Free end; Total length: 1; m Technologie: KNX; Coding: F; Mating force of a plug-in connection: approx. 10 ... 15 N; Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N; Number of mating cycles: $i \geq 200$; Connection type: Socket - free end; Type of pre-assembled cable: Connecting cable; Cable type: J-Y(ST)Y...LG 1x2x0.8; Marking: 1+ 2-; Protection type: IP20; Note on protection type: Only when mated and secured with a strain relief housing (These compact connectors are not designed for use in open, easily accessible areas.); Potential marking: 1+ 2-; Application: KNX; Mismating protection: Yes; Locking of plug-in connection: locking lever; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Dca; Contact material: Copper alloy (surface-treated); Fire load: 0,15; MJ Connector Culoare: light gray; Strain relief Culoare: black; Sheathed cable Culoare: gray; Halogen-free: Yes; Greutate: 39,6; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: DE; GTIN: 4055143536578; Customs tariff number: 85444290900; Pret: 69,50 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/pre-assembled-connecting-cable-socket-open-ended-2-pole-cod-f-1-m-gray-133472
---	--