

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 4-LEVEL SAME POTENTIAL TERMINAL BLOCK; FOR 35 X 7.5
MOUNTING RAIL; 1,50 MM²; LIGHT GRAY**

Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 18; A
Legend (ratings): (III / 3) \hat{a} %TM Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0.08 ... 1.5 mm² / 28 ... 16 AWG;
Fine-stranded conductor: 0.08 ... 1.5 mm² / 28 ... 16 AWG;
Strip length: 8 ... 10 mm / 0.31 ... 0.39 inch;
Numar total de conexiuni: 16;
Total number of potentials: 1;
Numar nivele: 4;
Wiring type: Front-entry wiring;
Latime: 7.62 mm / 0.3 inch;
Inaltime from upper-edge of DIN-rail: 62 mm / 2.441 inch;
Adancime: 126 mm / 4.961 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking: 0-1-2-3--3-2-1-0;
Marking level: Center marking;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,576; MJ
Greutate: 30,3; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454189136;
Customs tariff number: 85369010000;
Pret: 52,88 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-level-same-potential-terminal-block-for-35-x-7-5-mounting-rail-1-50-mm2-light-gray-134352>