

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

**WAGO FEMALE CONNECTOR FOR RAIL-MOUNT TERMINAL BLOCKS;
 0.6 X 1 MM PINS; STRAIGHT; 100% PROTECTED AGAINST
 MISMATING; LOCKING LEVER; PIN SPACING 5 MM; 12-POLE; LIGHT
 GRAY**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 320; V
 Tensiune nominala de supratensiune (III/3): 4; kV
 Tensiune nominala (III/2): 320; V
 Tensiune nominala de supratensiune (III/2): 4; kV
 Tensiune nominala (II/2): 630; V
 Tensiune nominala de supratensiune (II/2): 4; kV
 Curent nominal: 12; A
 Legend (ratings): (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 300; V
 Curent nominal UL (Use Group B): 15; A
 Tensiune nominala UL (Use Group D): 300; V
 Curent nominal UL (Use Group D): 10; A
 Certificari: UL 1059;
 Tensiune nominala UL 1977: 600; V
 Curent nominal UL 1977: 15; A
 Tensiune nominala CSA (Use Group B): 300; V
 Curent nominal CSA (Use Group B): 15; A
 Tensiune nominala CSA (Use Group D): 300; V
 Curent nominal CSA (Use Group D): 10; A
 Numar poli: 12;
 Total number of potentials: 12;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 1;
 Distanta intre pini: 5 mm / 0.197 inch;
 Latime: 75,8 mm / 2.984 inch;
 Inaltime: 36,1 mm / 1.421 inch;
 Inaltime de la fata: 21,6 mm / 0.85 inch;
 Adancime: 11,6 mm / 0.457 inch;
 Tip contact (pluggable connector): Conector mama/priza;
 Connector (connection type): for front-entry rail-mount terminal block;
 Mismatching protection: Yes;
 Locking of plug-in connection: locking lever;
 Mating direction to the rail-mount terminal block: 90; °
 Culoare: light gray;
 Material group: I;
 Material izolator: Polyamide 66 (PA 66);
 Flammability class per UL94: V0;
 Contact material: Copper alloy;
 Contact plating: tin-plated;
 Greutate: 13,5; g
 Temperatura lucru: -60 ... +85 °C;
 Tip ambalare: BOX;
 Tara de origine: DE;
 GTIN: 4055143372909;
 Customs tariff number: 85366990990;
 Pret: 52,30 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/female-connector-for-rail-mount-terminal-blocks-0-6-x-1-mm-pins-straight-100-protected-against-mismatching-locking-lever-pin-spacing-5-mm-12-pole-light-gray-134564>