

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

<p>Technical drawing of a WAGO 1-conductor male connector. It includes front, side, and detail views with the following dimensions: 4.1, 5, 10.5, 15 ±0.1, 17.5, 14.4, 27.3, 13.3, 1.5, 1.2, and L<sub>a</sub> ±0.1.</p>	<p align="center"><b>WAGO 1-CONDUCTOR MALE CONNECTOR; 100% PROTECTED AGAINST MISMATING; SNAP-IN FLANGE; 2.5 MM<sup>2</sup>; PIN SPACING 5 MM; 16-POLE; 2,50 MM<sup>2</sup>; LIGHT GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;          Tensiune nominala (III/3): 320; V          Tensiune nominala de supratensiune (III/3): 4; kV          Tensiune nominala (III/2): 320; V          Tensiune nominala de supratensiune (III/2): 4; kV          Tensiune nominala (II/2): 630; V          Tensiune nominala de supratensiune (II/2): 4; kV          Curent nominal: 12; A          Legend (ratings): (III / 2) %<sup>TM</sup> Overvoltage category III / Pollution degree 2;          Tensiune nominala UL (Use Group B): 300; V          Curent nominal UL (Use Group B): 15; A          Tensiune nominala UL (Use Group D): 300; V          Curent nominal UL (Use Group D): 10; A          Certificari: UL 1059;          Tensiune nominala UL 1977: 600; V          Curent nominal UL 1977: 15; A          Tensiune nominala CSA (Use Group B): 300; V          Curent nominal CSA (Use Group B): 15; A          Tensiune nominala CSA (Use Group D): 300; V          Curent nominal CSA (Use Group D): 10; A          Tehnologie conexiune: CAGE CLAMP®;          Tip actionare: Operating tool;          Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;          Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;          Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;          Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm<sup>2</sup>;          Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;          Numar poli: 16;          Numar total de conexiuni: 16;          Total number of potentials: 16;          Numar tipuri de conexiuni: 1;          Numar nivele: 1;          Conductor entry direction to mating direction: 0; °          Distanta intre pini: 5 mm / 0.197 inch;          Latime: 101 mm / 3.976 inch;          Inaltime: 17.5 mm / 0.689 inch;          Adancime: 27.5 mm / 1.083 inch;          Housing sheet thickness: 0.5 ... 2.5 mm / 0.02 ... 0.098 inch;          Tip montaj: Snap-in;          Tip montaj: Feed-through mounting;          Tip contact (pluggable connector): Conector tata/fisa;          Connector (connection type): for conductors;          Mismatching protection: Yes;          Culoare: light gray;          Material group: I;          Material izolator: Polyamide 66 (PA 66);          Flammability class per UL94: V0;          Clamping spring material: Chrome nickel spring steel (CrNi);          Contact material: Cupru electrolitic (ECu);          Contact plating: tin-plated;          Fire load: 0,483; MJ          Greutate: 26,1; g          Temperatura lucru: -60 ... +100 °C;          Product Group: 3 (Multi Conn. System);          Tip ambalare: BOX;          Tara de origine: DE;          GTIN: 4050821280217;          Customs tariff number: 85366990990;          Pret: 58,40 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/1-conductor-male-connector-100-protected-against-mismatching-snap-in-flange-2-5-mm2-pin-spacing-5-mm-16-pole-2-50-mm2-light-gray-134591">https://www.materialelectrice.ro/1-conductor-male-connector-100-protected-against-mismatching-snap-in-flange-2-5-mm2-pin-spacing-5-mm-16-pole-2-50-mm2-light-gray-134591</a></p>
--	--