

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-ENDED; 2-POLE; COD. B; CONTROL CABLE 2 X 1.5 MM²; 2 M; 1,50 MM²; PINK

Note on Contact Resistance: approx. 1 m Ω ; of contact resistance \hat{c} approx. 0.25 m Ω ;
contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) \hat{a} %TM Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 14; A
Numar poli: 2;
Total number of potentials: 2;
Conductor preparation: tip-bonded;
Sheathed cable diameter: 6,8 ... 8,6 mm;
Sectiunea transversala a firului: 1,5; mm²
Strip length (outer insulation): 32; mm
Connection type: Plug - Free end;
Distanta intre pini: 4,4 mm / 0.173 inch;
Total length: 2; m
Coding: B;
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);
Number of mating cycles: \hat{i} 200, without resistive load100, with resistive load IN = 16 A, tested (1.5 mm²/16 AWG);
Connection type: Plug - Free end;
Type of pre-assembled cable: Connecting cable;
Cable type: Control line 2 x 1.5;
Marking: 1 2;
Protection type: IP20;
Note on protection type: IP40 when mated;
Potential marking: 1 2;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: pink;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Connector Culoare: pink;
Printing color of mating face: black;
Strain relief Culoare: black;
Printing color of strain relief: white;
Sheathed cable Culoare: gray;
Printing color of sheathed cable: black;
Sheath material: PVC;
Greutate: 134,5; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures \leq 70 °C (including halogen-free) Insulating parts for temperatures \leq 105 °C;
Tip ambalare: not packed;
Tara de origine: PL;
GTIN: 4055143511568;
Customs tariff number: 85444290900;
Pret: 29,25 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-2-pole-cod-b-control-cable-2-x-1-5-mm2-2-m-1-50-mm2-pink-135101>