


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO 1-CONDUCTOR FEMALE CONNECTOR, 2-ROW; 100%
 PROTECTED AGAINST MISMATING; SCREW FLANGE; STRAIN RELIEF
 PLATE; 1.5 MM²; PIN SPACING 3.5 MM; 10-POLE; 1,50 MM²;
 BLACK**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 80; V
 Tensiune nominala de supratensiune (III/3): 2,5; kV
 Tensiune nominala (III/2): 160; V
 Tensiune nominala de supratensiune (III/2): 2,5; kV
 Tensiune nominala (II/2): 250; V
 Tensiune nominala de supratensiune (II/2): 2,5; kV
 Curent nominal: 10; A
 Legend (ratings): (III / 2) \hat{a} %TM Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 300; V
 Curent nominal UL (Use Group B): 10; A
 Tensiune nominala UL (Use Group C): 50; V
 Curent nominal UL (Use Group C): 10; A
 Certificari: UL 1059;
 Tensiune nominala CSA (Use Group B): 300; V
 Curent nominal CSA (Use Group B): 10; A
 Tehnologie conexiune: CAGE CLAMP®;
 Tip actionare: Operating tool;
 Solid conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;
 Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 1 mm²;
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1 mm²;
 Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;
 Numar poli: 10;
 Numar total de conexiuni: 10;
 Total number of potentials: 10;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 2;
 Conductor entry direction to mating direction: 0; °
 Distanta intre pini: 3,5 mm / 0.138 inch;
 Latime: 27,6 mm / 1.087 inch;
 Inaltime: 38,7 mm / 1.524 inch;
 Adancime: 16 mm / 0.63 inch;
 Tip contact (pluggable connector): Conector mama/priza;
 Connector (connection type): for conductor;
 Mismatching protection: Yes;
 Locking of plug-in connection: Screw flange;
 Strain relief: strain relief plate;
 Culoare: black;
 Material group: II;
 Material izolator: Glass fiber-reinforced polyamide (PA°66°GF);
 Flammability class per UL94: V0;
 Clamping spring material: Chrome nickel spring steel (CrNi);
 Contact material: Copper alloy;
 Contact plating: tin-plated;
 Greutate: 6,6; g
 Temperatura lucru: -60 ... +100 °C;
 Tip ambalare: BOX;
 Tara de origine: PL;
 GTIN: 4055143456623;
 Customs tariff number: 85366990990;
 Pret: 44,42 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-connector-2-row-100-protected-against-mismatching-screw-flange-strain-relief-plate-1-5-mm2-pin-spacing-3-5-mm-10-pole-1-50-mm2-black-135223>