

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO PCB TERMINAL BLOCK; LEVER; 6 MM²; PIN SPACING 10 MM; 11-POLE; CAGE CLAMP[®]; COMMONING OPTION; 6,00 MM²; GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 800; V Tensiune nominala de supratensiune (III/3): 8; kV Tensiune nominala (III/2): 1000; V Tensiune nominala de supratensiune (III/2): 8; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 8; kV Curent nominal: 41; A Legend (ratings): (III / 2) $\hat{=}$ ∞™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 30; A Tensiune nominala UL (Use Group C): 300; V Curent nominal UL (Use Group C): 30; A Tensiune nominala UL (Use Group D): 600; V Curent nominal UL (Use Group D): 5; A Certificari: UL 1059; Tehnologie conexiune: CAGE CLAMP[®]; Tip actionare: Lever; Solid conductor: 0,5 ... 6 mm² / 20 ... 10 AWG; Fine-stranded conductor: 0,5 ... 6 mm² / 20 ... 10 AWG; Fine-stranded conductor; with insulated ferrule: 0,5 ... 6 mm²; Fine-stranded conductor; with uninsulated ferrule: 0,5 ... 6 mm²; Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch; Conductor connection direction to PCB: 30; ° Numar poli: 11; Numar total de conexiuni: 11; Total number of potentials: 11; Numar tipuri de conexiuni: 1; Numar nivele: 1; Number of jumper slots: 1; Distanta intre pini: 10 mm / 0.394 inch; Latime: 107,5 mm / 4.232 inch; Inaltime: 30 mm / 1.181 inch; Inaltime de la fata: 25,5 mm / 1.004 inch; Adancime: 30 mm / 1.181 inch; Lungimea pinului de contact: 4,5; mm Solder pin dimensions: 1 x 1,4 mm; Diametrul de gaurire cu toleranta: 1,8 (+0,1) mm; PCB contact: THT; Solder pin arrangement: over the entire terminal strip (in-line); Number of solder pins per potential: 2; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic (ECu); Contact plating: tin-plated; Fire load: 1,527; MJ Greutate: 74,5; g Temperatura lucru: -60 ... +105 °C; Product Group: 4 (Printed Circuit); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4050821093428; Customs tariff number: 85369010000; Pret: 75,14 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/pcb-terminal-block-lever-6-mm2-pin-spacing-10-mm-11-pole-cage-clamp-commoning-option-6-00-mm2-gray-135649</p>
--	---