


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; ECA; SOCKET/PLUG; 2-POLE; COD. I; H05Z1Z1-F 2 X 1,50 MM²; 8 M; 1,50 MM²; BLUE</p> <p>Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 16; A Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 14; A Numar poli: 2; Total number of potentials: 2; Conductor preparation: tip-bonded; Sheathed cable diameter: 6,8 ... 8,6 mm; Sectiunea transversala a firului: 1,5; mm² Connection type: Socket - Plug; Distanta intre pini: 4,4 mm / 0.173 inch; Total length: 8; m Technologie: DALI; Coding: I; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: î»¿200, without resistive load100, with resistive load IN = 16 A, tested (1.5mm²/AWG 16); Connection type: Socket - Plug; Type of pre-assembled cable: Interconnecting cable; Cable type: H05Z1Z1-F 2x1.5; Marking: + -; Protection type: IP20; Note on protection type: IP40 when mated; Potential marking: + -; Application: Lighting management; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: retrofittable; Culoare: blue; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper or copper alloy (surface-treated); Fire load: 14,138; MJ Connector Culoare: blue; Printing color of mating face: black; Strain relief Culoare: white; Printing color of strain relief: black; Sheathed cable Culoare: white; Printing color of sheathed cable: black; Halogen-free: Yes; Greutate: 564; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: PL; GTIN: 4055143392549; Customs tariff number: 85444290900; Pret: 84,21 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/pre-assembled-interconnecting-cable-eca-socket-plug-2-pole-cod-i-h05z1z1-f-2-x-1-50-mm2-8-m-1-50-mm2-blue-135707</p>
-----------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------