

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO 4-CONDUCTOR TERMINAL STRIP; SUITABLE FOR EX E II APPLICATIONS; 9-POLE; WITHOUT PUSH-BUTTONS; WITH FIXING FLANGES; FOR SCREW OR SIMILAR MOUNTING TYPES; FIXING HOLE 3.2 MM Å~; 2.5 MMÂ²; CAGE CLAMPÂ®; 2,50 MMÂ²; LIGHT GRAY

Tensiune nominala EN (Ex e II): 690; V
Curent nominal (Ex e II): 23; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 9;
Numar total de conexiuni: 36;
Total number of potentials: 9;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): 12 AWG: THHN, THWN;
Latime: 106 mm / 4.173 inch;
Inaltime de la fata: 22.1 mm / 0.87 inch;
Adancime: 32 mm / 1.26 inch;
Module Latime: 10 mm / 0.394 inch;
Design: horizontal;
Marking level: Center marking;
Culoare: light gray;
Fire load: 1,073; MJ
Greutate: 58,9; g
Product Group: 9 (Std. Chassis Mt. Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918415736;
Customs tariff number: 85369010000;
Pret: 63,32 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-terminal-strip-suitable-for-ex-e-ii-applications-9-pole-without-push-buttons-with-fixing-flanges-for-screw-or-similar-mounting-types-fixing-hole-3-2-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-light-gray-135770>