

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

| | |
|--|---|
| | <p>WAGO PCB TERMINAL BLOCK; 16 MM²; PIN SPACING 15 MM; 8-POLE; PUSH-IN CAGE CLAMP®; 16,00 MM²; GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 1000; V Tensiune nominala de supratensiune (III/3): 8; kV Tensiune nominala (III/2): 1000; V Tensiune nominala de supratensiune (III/2): 8; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 8; kV Curent nominal: 76; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 85; A Tensiune nominala UL (Use Group C): 300; V Curent nominal UL (Use Group C): 85; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0.75 ... 16 mm² / 18 ... 4 AWG; Fine-stranded conductor: 0.75 ... 25 mm² / 18 ... 4 AWG; Fine-stranded conductor; with insulated ferrule: 0.75 ... 16 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.75 ... 16 mm²; Fine-stranded conductor; with twin ferrule: 0.75 ... 6 mm²; Strip length: 18 ... 20 mm / 0.71 ... 0.79 inch; Conductor connection direction to PCB: 90; ° Numar poli: 8; Numar total de conexiuni: 8; Total number of potentials: 8; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 15 mm / 0.591 inch; Latime: 116.6 mm / 4.591 inch; Inaltime: 35.3 mm / 1.39 inch; Inaltime de la fata: 31.3 mm / 1.232 inch; Adancime: 24.8 mm / 0.976 inch; Lungimea pinului de contact: 4; mm Solder pin dimensions: 1.2 x 1 mm; Diametrul de gaurire cu toleranta: 1.7 (+0.1) mm; Tip montaj: Feed-through mounting; PCB contact: THT; Solder pin arrangement: over the entire terminal strip, in line; Number of solder pins per potential: 6; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic (ECu); Contact plating: tin-plated; Greutate: 78,9; g Temperatura lucru: -60 ... +105 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4055143861540; Customs tariff number: 85369010000; Pret: 124,26 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/pcb-terminal-block-16-mm2-pin-spacing-15-mm-8-pole-push-in-cage-clamp-16-00-mm2-gray-135784</p> |
|--|---|