

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO PCB TERMINAL BLOCK; 16 MM<sup>2</sup>; PIN SPACING 15 MM; 5-POLE; PUSH-IN CAGE CLAMP®; 16,00 MM<sup>2</sup>; GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;          Tensiune nominala (III/3): 1000; V          Tensiune nominala de supratensiune (III/3): 8; kV          Tensiune nominala (III/2): 1000; V          Tensiune nominala de supratensiune (III/2): 8; kV          Tensiune nominala (II/2): 1000; V          Tensiune nominala de supratensiune (II/2): 8; kV          Curent nominal: 76; A          Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2;          Tensiune nominala UL (Use Group B): 300; V          Curent nominal UL (Use Group B): 85; A          Tensiune nominala UL (Use Group C): 300; V          Curent nominal UL (Use Group C): 85; A          Certificari: UL 1059;          Tehnologie conexiune: Push-in CAGE CLAMP®;          Tip actionare: Operating tool;          Solid conductor: 0.75 ... 16 mm<sup>2</sup> / 18 ... 4 AWG;          Fine-stranded conductor: 0.75 ... 25 mm<sup>2</sup> / 18 ... 4 AWG;          Fine-stranded conductor; with insulated ferrule: 0.75 ... 16 mm<sup>2</sup>;          Fine-stranded conductor; with uninsulated ferrule: 0.75 ... 16 mm<sup>2</sup>;          Fine-stranded conductor; with twin ferrule: 0.75 ... 6 mm<sup>2</sup>;          Strip length: 18 ... 20 mm / 0.71 ... 0.79 inch;          Conductor connection direction to PCB: 90; °          Numar poli: 5;          Numar total de conexiuni: 5;          Total number of potentials: 5;          Numar tipuri de conexiuni: 1;          Numar nivele: 1;          Distanta intre pini: 15 mm / 0.591 inch;          Latime: 71.6 mm / 2.819 inch;          Inaltime: 35.3 mm / 1.39 inch;          Inaltime de la fata: 31.3 mm / 1.232 inch;          Adancime: 24.8 mm / 0.976 inch;          Lungimea pinului de contact: 4; mm          Solder pin dimensions: 1.2 x 1 mm;          Diametrul de gaurire cu toleranta: 1.7 (+0.1) mm;          Tip montaj: Feed-through mounting;          PCB contact: THT;          Solder pin arrangement: over the entire terminal strip, in line;          Number of solder pins per potential: 6;          Culoare: gray;          Material group: I;          Material izolator: Polyamide 66 (PA 66);          Flammability class per UL94: V0;          Clamping spring material: Chrome nickel spring steel (CrNi);          Contact material: Cupru electrolitic(ESu);          Contact plating: tin-plated;          Greutate: 49,1; g          Temperatura lucru: -60 ... +105 °C;          Tip ambalare: BOX;          Tara de origine: DE;          GTIN: 4055143861519;          Customs tariff number: 85369010000;          Pret: 74,74 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/pcb-terminal-block-16-mm2-pin-spacing-15-mm-5-pole-push-in-cage-clamp-16-00-mm2-gray-135789">https://www.materialelectrice.ro/pcb-terminal-block-16-mm2-pin-spacing-15-mm-5-pole-push-in-cage-clamp-16-00-mm2-gray-135789</a></p>
--	--