

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b><u>WAGO PCB TERMINAL BLOCK; 6 MM<sup>2</sup>; PIN SPACING 7.5 MM; 5-POLE; PUSH-IN CAGE CLAMP®; 6,00 MM<sup>2</sup>; GRAY</u></b></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 800; V Tensiune nominala de supratensiune (III/3): 8; kV Tensiune nominala (III/2): 1000; V Tensiune nominala de supratensiune (III/2): 8; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 8; kV Curent nominal: 48; A Legend (ratings): (III / 2) <math>\hat{a}</math>%™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 600; V Curent nominal UL (Use Group B): 38; A Tensiune nominala UL (Use Group C): 600; V Curent nominal UL (Use Group C): 38; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG; Fine-stranded conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG; Fine-stranded conductor; with insulated ferrule: 0,25 ... 6 mm<sup>2</sup>; Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 6 mm<sup>2</sup>; Fine-stranded conductor; with twin ferrule: 0,25 ... 2,5 mm<sup>2</sup>; Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch; Conductor connection direction to PCB: 0; ° Numar poli: 5; Numar total de conexiuni: 5; Total number of potentials: 5; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 7,5 mm / 0.295 inch; Latime: 39,3 mm / 1.547 inch; Inaltime: 23,6 mm / 0.929 inch; Inaltime de la fata: 19,6 mm / 0.772 inch; Adancime: 24,2 mm / 0.953 inch; Lungimea pinului de contact: 4; mm Solder pin dimensions: 1,5 x 1 mm; Diametrul de gaurire cu toleranta: 2 (+0,1) mm; Tip montaj: Feed-through mounting; PCB contact: THT; Solder pin arrangement: over the entire terminal strip, staggered; Number of solder pins per potential: 1; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ESu); Contact plating: tin-plated; Greutate: 19,8; g Temperatura lucru: -60 ... +105 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4055143587129; Customs tariff number: 85369010000; Pret: 34,51 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/pcb-terminal-block-6-mm2-pin-spacing-7-5-mm-5-pole-push-in-cage-clamp-6-00-mm2-gray-135877">https://www.materialelectrice.ro/pcb-terminal-block-6-mm2-pin-spacing-7-5-mm-5-pole-push-in-cage-clamp-6-00-mm2-gray-135877</a></p>
--	---