

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410




Plate thickness: 0.5 ... 2 mm
 Cutout tolerance: + 0.1 mm

WAGO SNAP-IN PLUG; 5-POLE; COD. B; 1,50 MM²; PINK

Note on Contact Resistance: approx. 1 mΩ; of contact resistance © approx. 0.25 mΩ;
 contact transition plug/socket;
 Ratings per: IEC/EN 60664-1;
 Tesiune nominala (III/3): 400; V
 Tensiune nominala de supratensiune (III/3): 6; kV
 Curent nominal: 16; A
 Note on Curent nominal: 13 A for 3-pole load 10 A for 4- and 5-pole load;
 Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;
 Tensiune nominala UL 1977: 600; V
 Curent nominal UL 1977: 12; A
 Tehnologie conexiune: Push-in CAGE CLAMP®;
 Tip actionare: Operating tool; Push-in;
 Nominal cross-section: 1,5 mm²;
 Solid conductor: 0,25 ... 1,5 mm² / 22 ... 16 AWG;
 Solid conductor; push-in termination: 0,75 ... 1,5 mm² / 20 ... 16 AWG;
 Stranded conductor: 0,25 ... 1 mm² / 22 ... 18 AWG;
 Fine-stranded conductor: 0,25 ... 1,5 mm² / 22 ... 16 AWG;
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 0,75 mm² / 22 ... 20 AWG;
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 0,75 mm² / 22 ... 20 AWG;
 Fine-stranded conductor; with ferrule; push-in termination: 0,75 mm² / 20 AWG;
 Strip length: 9 mm / 0.35 inch;
 Note (strip length): see also packaging or instructions;
 Numar poli: 5;
 Numar total de conexiuni: 5;
 Total number of potentials: 5;
 Conductor entry direction to mating direction: 0; °
 Distanta intre pini: 4,4 mm / 0.173 inch;
 Latime: 35,5 mm / 1.398 inch;
 Inaltime: 17,5 mm / 0.689 inch;
 Adancime: 39,85 mm / 1.569 inch;
 Coding: B;
 Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
 Retention force of a plug-in connection: Locked: > 80 N;
 Unmating force of a plug-in connection: Unlocked: approx. 20 ... 70 N (depending on pole number);
 Number of mating cycles: >200, without resistive load 100, with resistive load IN = 16 A, tested (1.5 mm²/16 AWG);
 Housing sheet thickness: 0,5 ... 2 mm / 0.02 ... 0.079 inch;
 Tip montaj: Snap-in;
 Marking: N š L - +;
 Protection type: IP20;
 Note on protection type: IP40 when mated;
 Potential marking: N š L - +;
 Tip contact (pluggable connector): Conector tata/fisa;
 Connector (connection type): for conductor;
 Mismatching protection: Yes;
 Locking of plug-in connection: locking lever;
 Locking lever: yes;
 Culoare: pink;
 Material izolator: Polyamide 66 (PA 66);
 Clamping spring material: Chrome nickel spring steel (CrNi);
 Contact material: Copper or copper alloy (surface-treated);
 Greutate: 8; g
 Processing temperature: -5 ... +40 °C;
 Continuous operating temperature: -35 ... +85 °C;
 Note on continuous operating temperature: Insulating parts for temperatures ≤ 105 °C;
 Tip ambalare: BOX;
 Tara de origine: PL;
 GTIN: 4055143428255;
 Customs tariff number: 85366990990;
 Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/snap-in-plug-5-pole-cod-b-1-50-mm2-pink-135883>