

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; 2-POLE;  
N-L1; WITHOUT GROUND CONTACT; FOR SELF-TAPPING SCREW 2.9  
MM Ø FROM BELLOW; WITH 2X PIN; 4 MM<sup>2</sup>; 4,00 MM<sup>2</sup>; WHITE**

Tesiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) %<sup>o</sup>™ Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Operating tool; Push-button;  
Connectable conductor materials: Copper;  
Solid conductor: 0,5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Stranded conductor: 0,5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor: 0,5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,5 ... 2,5 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 0,75 mm<sup>2</sup> / 18 AWG;  
Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;  
Numar poli: 2;  
Numar total de conexiuni: 8;  
Total number of potentials: 2;  
Wiring type: Side-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Distanta intre pini: 12 mm / 0.472 inch;  
Latime: 24 mm / 0.945 inch;  
Inaltime de la fata: 22,3 mm / 0.878 inch;  
Adancime: 35 mm / 1.378 inch;  
Tip montaj: Screw mounting;  
Marking: N-L1;  
Culoare: white;  
Fire load: 0,267; MJ  
Greutate: 14,1; g  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4044918510318;  
Customs tariff number: 85369010000;  
Pret: 8,95 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-chassis-mount-terminal-strip-2-pole-n-l1-without-ground-contact-for-self-tapping-screw-2-9-mm-oe-from-bellow-with-2x-pin-4-mm2-4-00-mm2-white-136189>