


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO THR PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN
SPACING 3.5 MM; 3-POLE; PUSH-IN CAGE CLAMP®; IN TAPE-AND-
REEL PACKAGING; 1,50 MM²; BLACK**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 200; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tensiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 17,5; A
Legend (ratings): (III / 2) $\hat{\%}$ ™ Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group C): 150; V
Curent nominal UL (Use Group C): 10; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-button;
Solid conductor: 0,2 ... 1,5 mm² / 24 ... 16 AWG;
Fine-stranded conductor: 0,2 ... 1,5 mm² / 24 ... 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 ... 1 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1 mm²;
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 3;
Total number of potentials: 3;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3,5 mm / 0.138 inch;
Inaltime: 12,7 mm / 0.5 inch;
Inaltime de la fata: 10,5 mm / 0.413 inch;
Adancime: 13,6 mm / 0.535 inch;
Lungimea pinului de contact: 2,2; mm
Solder pin dimensions: 0,5 x 0,75 mm;
Diametru placat prin gaura (THR): 1,1 (+0,1) mm;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 32; mm
PCB contact: THR;
Solder pin arrangement: over the entire terminal strip (staggered);
Number of solder pins per potential: 2;
Culoare: black;
Material group: III a;
Material izolator: Polyamide 46 (PA 46);
Flammability class per UL94: V2;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic (ECu);
Contact plating: tin-plated;
Greutate: 2; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143235389;
Customs tariff number: 85369010000;
Pret: 6,57 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/thr-pcb-terminal-block-push-button-1-5-mm2-pin-spacing-3-5-mm-3-pole-push-in-cage-clamp-in-tape-and-reel-packaging-1-50-mm2-black-136423>