

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-  
ENDED; 4-POLE; COD. A; H05VV-F 4G 1.5 MM<sup>2</sup>; 1 M; 1,50 MM<sup>2</sup>;  
WHITE**

Note on Contact Resistance: approx. 1 m $\Omega$ ; of contact resistance $\hat{c}$  approx. 0.25 m $\Omega$ ;  
contact transition plug/socket;  
Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Curent nominal: 16; A  
Legend (ratings): (III / 3)  $\hat{a}$ ™ Overvoltage category III / Pollution degree 3;  
Strip length: 9 mm / 0.35 inch;  
Numar poli: 4;  
Total number of potentials: 4;  
Conductor preparation: tip-bonded;  
Sheathed cable diameter: 8,4 ... 10,5 mm;  
Sectiunea transversala a firului: 1,5; mm<sup>2</sup>  
Strip length (outer insulation): 55; mm  
Connection type: Plug - Free end;  
Total length: 1; m  
Coding: A;  
Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);  
Retention force of a plug-in connection: when locked: > 80N;  
Unmating force of a plug-in connection: when unlocked: approx. 30 ... 70 N (depending  
on pole number);  
Number of mating cycles:  $\hat{i}$ 200, without resistive load100, with resistive load IN = 20  
A, tested (2.5mm<sup>2</sup>/AWG 14);  
Connection type: Plug - free end;  
Type of pre-assembled cable: Connecting cable;  
Cable type: H05VV-F 4G1.5;  
Marking: N  $\hat{a}$ š 2 1;  
Protection type: IP20;  
Note on protection type: Only when mated (these compact connectors are not designed  
for use in open, easily accessible areas.);  
Application: General mains applications;  
Mismating protection: Yes;  
Locking of plug-in connection: locking lever;  
Culoare: white;  
Material izolator: Polyamide 66 (PA 66);  
Fire class per EN 50575: Eca;  
Contact material: Copper or copper alloy (surface-treated);  
Fire load: 2,269; MJ  
Connector Culoare: white;  
Strain relief Culoare: white;  
Sheath material: PVC;  
Greutate: 133,7; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: PVC cable for temperatures  $\leq$  70 °C  
(including halogen-free) Insulating parts for temperatures  $\leq$  105 °C;  
Tip ambalare: not packed;  
Tara de origine: DE;  
GTIN: 4045454346263;  
Customs tariff number: 85444290900;  
Pret: 53,49 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-4-pole-cod-a-h05vv-f-4g-1-5-mm2-1-m-1-50-mm2-white-136579>