


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO STACKABLE PCB TERMINAL BLOCK; PUSH-BUTTON; 2.5  
MM<sup>2</sup>; PIN SPACING 7.5/7.62 MM; 1-POLE; CAGE CLAMP<sup>®</sup>;  
COMMONING OPTION; 2,50 MM<sup>2</sup>; RED**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Tensiune nominala (III/2): 630; V  
Tensiune nominala de supratensiune (III/2): 6; kV  
Tensiune nominala (II/2): 1000; V  
Tensiune nominala de supratensiune (II/2): 6; kV  
Curent nominal: 24; A  
Legend (ratings): (III / 2)  $\hat{\%}$ ™ Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group B): 300; V  
Curent nominal UL (Use Group B): 15; A  
Tensiune nominala UL (Use Group D): 300; V  
Curent nominal UL (Use Group D): 10; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group B): 300; V  
Curent nominal CSA (Use Group B): 15; A  
Tensiune nominala CSA (Use Group D): 300; V  
Curent nominal CSA (Use Group D): 10; A  
Tehnologie conexiune: CAGE CLAMP<sup>®</sup>;  
Tip actionare: Push-button;  
Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;  
Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;  
Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;  
Conductor connection direction to PCB: 90; °  
Numar poli: 1;  
Numar total de conexiuni: 1;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Distanta intre pini: 7.5/7.62 mm / 0.295/0.3 inch;  
Latime: 10.3 mm / 0.406 inch;  
Inaltime: 18.2 mm / 0.717 inch;  
Inaltime de la fata: 14.2 mm / 0.559 inch;  
Adancime: 18.3 mm / 0.72 inch;  
Lungimea pinului de contact: 4; mm  
Solder pin dimensions: 0.7 x 0.7 mm;  
Diametrul de gaurire cu toleranta: 1.1 (+0.1) mm;  
PCB contact: THT;  
Solder pin arrangement: within the terminal block, in line;  
Number of solder pins per potential: 2;  
Culoare: red;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic (ECu);  
Contact plating: tin-plated;  
Fire load: 0,023; MJ  
Greutate: 1,4; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4044918663182;  
Customs tariff number: 85369010000;  
Pret: 2,15 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/stackable-pcb-terminal-block-push-button-2-5-mm2-pin-spacing-7-5-7-62-mm-1-pole-cage-clamp-commoning-option-2-50-mm2-red-136745>