

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

|  |  |
|--|--|
|  | <p><b>WAGO 2-CONDUCTOR PCB TERMINAL BLOCK; 0.75 MM<sup>2</sup>; PIN SPACING 10/10.16 MM; 2-POLE; PUSH WIRE<sup>®</sup>; 0.75 MM<sup>2</sup>; GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;<br/>Tensiune nominala (III/3): 630; V<br/>Tensiune nominala de supratensiune (III/3): 8; kV<br/>Tensiune nominala (III/2): 1000; V<br/>Tensiune nominala de supratensiune (III/2): 8; kV<br/>Tensiune nominala (II/2): 1000; V<br/>Tensiune nominala de supratensiune (II/2): 8; kV<br/>Curent nominal: 10; A<br/>Legend (ratings): (III / 2) <sup>â%</sup>™ Overvoltage category III / Pollution degree 2;<br/>Tensiune nominala UL (Use Group B): 300; V<br/>Curent nominal UL (Use Group B): 10; A<br/>Tensiune nominala UL (Use Group D): 300; V<br/>Curent nominal UL (Use Group D): 10; A<br/>Certificari: UL 1059;<br/>Tensiune nominala CSA (Use Group B): 300; V<br/>Curent nominal CSA (Use Group B): 10; A<br/>Tensiune nominala CSA (Use Group D): 300; V<br/>Curent nominal CSA (Use Group D): 10; A<br/>Tehnologie conexiune: PUSH WIRE<sup>®</sup>;<br/>Tip actionare: Operating tool;<br/>Solid conductor: 0.25 ... 0.75 mm<sup>2</sup> / 22 ... 18 AWG;<br/>Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;<br/>Conductor connection direction to PCB: 45; °<br/>Numar poli: 2;<br/>Numar total de conexiuni: 4;<br/>Total number of potentials: 2;<br/>Numar tipuri de conexiuni: 1;<br/>Numar nivele: 1;<br/>Distanta intre pini: 10/10.16 mm / 0.394/0.4 inch;<br/>Latime: 21.5 mm / 0.846 inch;<br/>Inaltime: 20.5 mm / 0.807 inch;<br/>Inaltime de la fata: 16.5 mm / 0.65 inch;<br/>Adancime: 13.5 mm / 0.531 inch;<br/>Lungimea pinului de contact: 4; mm<br/>Solder pin dimensions: 0.5 x 0.75 mm;<br/>Diametrul de gaurire cu toleranta: 1.1 (+0.1) mm;<br/>PCB contact: THT;<br/>Solder pin arrangement: over the entire terminal strip, in line;<br/>Number of solder pins per potential: 2;<br/>Culoare: gray;<br/>Material group: I;<br/>Material izolator: Polyamide 66 (PA 66);<br/>Flammability class per UL94: V0;<br/>Clamping spring material: Chrome nickel spring steel (CrNi);<br/>Contact material: Cupru electrolitic(ECu);<br/>Contact plating: tin-plated;<br/>Fire load: 0,072; MJ<br/>Greutate: 3,4; g<br/>Temperatura lucru: -60 ... +105 °C;<br/>Product Group: 4 (Printed Circuit);<br/>Tip ambalare: BOX;<br/>Tara de origine: PL;<br/>GTIN: 4044918941891;<br/>Customs tariff number: 85369010000;<br/>Pret: 3,76 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-10-10-16-mm-2-pole-push-wire-0-75-mm2-gray-136904">https://www.materialelectrice.ro/2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-10-10-16-mm-2-pole-push-wire-0-75-mm2-gray-136904</a></p> |
|--|--|