


Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**WAGO PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM<sup>2</sup>; PIN  
 SPACING 7.5 MM; 5-POLE; PUSH-IN CAGE CLAMP®; 1.50 MM<sup>2</sup>;  
 ORANGE**

Ratings per: IEC/EN 60664-1;  
 Tensiune nominala (III/3): 500; V  
 Tensiune nominala de supratensiune (III/3): 6; kV  
 Tensiune nominala (III/2): 630; V  
 Tensiune nominala de supratensiune (III/2): 6; kV  
 Tensiune nominala (II/2): 1000; V  
 Tensiune nominala de supratensiune (II/2): 6; kV  
 Curent nominal: 17,5; A  
 Legend (ratings): (III / 2)  $\hat{a}$ %<sup>TM</sup> Overvoltage category III / Pollution degree 2;  
 Tensiune nominala UL (Use Group B): 300; V  
 Curent nominal UL (Use Group B): 10; A  
 Tensiune nominala UL (Use Group D): 300; V  
 Curent nominal UL (Use Group D): 2; A  
 Certificari: UL 1059;  
 Tensiune nominala CSA (Use Group B): 300; V  
 Curent nominal CSA (Use Group B): 10; A  
 Tensiune nominala CSA (Use Group D): 300; V  
 Curent nominal CSA (Use Group D): 10; A  
 Tehnologie conexiune: Push-in CAGE CLAMP®;  
 Tip actionare: Push-button;  
 Solid conductor: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 14 AWG;  
 Fine-stranded conductor: 0,75 ... 1,5 mm<sup>2</sup> / 18 ... 16 AWG;  
 Fine-stranded conductor; with insulated ferrule: 0,5 ... 1 mm<sup>2</sup>;  
 Fine-stranded conductor; with uninsulated ferrule: 0,5 ... 1 mm<sup>2</sup>;  
 Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
 Conductor connection direction to PCB: 45; °  
 Numar poli: 5;  
 Numar total de conexiuni: 5;  
 Total number of potentials: 5;  
 Numar tipuri de conexiuni: 1;  
 Numar nivele: 1;  
 Distanta intre pini: 7,5 mm / 0.295 inch;  
 Latime: 36,5 mm / 1.437 inch;  
 Inaltime: 20,5 mm / 0.807 inch;  
 Inaltime de la fata: 16,5 mm / 0.65 inch;  
 Adancime: 13 mm / 0.512 inch;  
 Lungimea pinului de contact: 4; mm  
 Solder pin dimensions: 0,5 x 0,75 mm;  
 Diametrul de gaurire cu toleranta: 1 (+0,1) mm;  
 PCB contact: THT;  
 Solder pin arrangement: over the entire terminal strip (in-line);  
 Number of solder pins per potential: 1;  
 Culoare: orange;  
 Material group: I;  
 Material izolator: Polyamide 66 (PA 66);  
 Flammability class per UL94: V0;  
 Clamping spring material: Chrome nickel spring steel (CrNi);  
 Contact material: Cupru electrolitic(ECu);  
 Contact plating: tin-plated;  
 Fire load: 0,141; MJ  
 Greutate: 6,1; g  
 Temperatura lucru: -60 ... +105 °C;  
 Product Group: 4 (Printed Circuit);  
 Tip ambalare: BOX;  
 Tara de origine: PL;  
 GTIN: 4044918304405;  
 Customs tariff number: 85369010000;  
 Pret: 8,24 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pcb-terminal-block-push-button-1-5-mm2-pin-spacing-7-5-mm-5-pole-push-in-cage-clamp-1-50-mm2-orange-136990>