

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO STACKABLE 2-CONDUCTOR PCB TERMINAL BLOCK; 0.75
MM²; PIN SPACING 7.5/7.62 MM; 1-POLE; SUITABLE FOR EX-I
APPLICATIONS; PUSH WIRE®; 0,75 MM²; BLUE**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Tensiune nominala (III/2): 630; V
Tensiune nominala de supratensiune (III/2): 6; kV
Tensiune nominala (II/2): 1000; V
Tensiune nominala de supratensiune (II/2): 6; kV
Curent nominal: 10; A
Legend (ratings): (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 10; A
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Operating tool;
Solid conductor: 0,25 ... 0,75 mm² / 24 ... 18 AWG;
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 0,34 mm²;
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 1;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 7,5/7,62 mm / 0.295/0.3 inch;
Latime: 9 mm / 0.354 inch;
Inaltime: 12,8 mm / 0.504 inch;
Inaltime de la fata: 9,2 mm / 0.362 inch;
Adancime: 12,5 mm / 0.492 inch;
Lungimea pinului de contact: 3,6; mm
Solder pin dimensions: 0,8 x 0,4 mm;
Diametrul de gaurire cu toleranta: 1 (+0,1) mm;
PCB contact: THT;
Solder pin arrangement: within the terminal block (in-line);
Number of solder pins per potential: 2;
Culoare: blue;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic (ECu);
Contact plating: tin-plated;
Fire load: 0,01; MJ
Greutate: 0,6; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4044918832052;
Pret: 1,61 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/stackable-2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-7-5-7-62-mm-1-pole-suitable-for-ex-i-applications-push-wire-0-75-mm2-blue-137361>