

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

<p>The drawing shows three views of the WAGO THT Female Header. The top view shows a 10-pole header with a 5.08 mm pin spacing. Dimensions include a total width of 65.6 mm, a height of 16.6 mm, and a mounting flange width of 11.6 mm. The side view shows a height of 18.25 mm and a mounting flange thickness of 4.4 mm. A detail view shows the solder pin dimensions: 0.6 mm diameter and 1 mm length.</p>	<p><b>WAGO THT FEMALE HEADER; 0.6 X 1.0 MM SOLDER PIN; ANGLED; SPACER FLANGE; PIN SPACING 5.08 MM; 10-POLE; ORANGE</b></p> <p>Ratings per: IEC/EN 60664-1;          Tensiune nominala (III/3): 320; V          Tensiune nominala de supratensiune (III/3): 4; kV          Tensiune nominala (III/2): 320; V          Tensiune nominala de supratensiune (III/2): 4; kV          Tensiune nominala (II/2): 630; V          Tensiune nominala de supratensiune (II/2): 4; kV          Curent nominal: 12; A          Legend (ratings): (III / 2) <math>\hat{a}</math>%<sup>TM</sup> Overvoltage category III / Pollution degree 2;          Tensiune nominala UL (Use Group B): 300; V          Curent nominal UL (Use Group B): 15; A          Tensiune nominala UL (Use Group D): 300; V          Curent nominal UL (Use Group D): 10; A          Certificari: UL 1059;          Tensiune nominala UL 1977: 600; V          Curent nominal UL 1977: 15; A          Tensiune nominala CSA (Use Group B): 300; V          Curent nominal CSA (Use Group B): 15; A          Tensiune nominala CSA (Use Group D): 300; V          Curent nominal CSA (Use Group D): 10; A          Numar poli: 10;          Total number of potentials: 10;          Numar tipuri de conexiuni: 1;          Numar nivele: 1;          Distanta intre pini: 5.08 mm / 0.2 inch;          Latime: 65.6 mm / 2.583 inch;          Inaltime: 16.6 mm / 0.654 inch;          Inaltime de la fata: 11.6 mm / 0.457 inch;          Adancime: 18.25 mm / 0.719 inch;          Lungimea pinului de contact: 5; mm          Solder pin dimensions: 0.6 x 1 mm;          Diametrul de gaurire cu toleranta: 1.3 (+0.1) mm;          Tip montaj: Mounting flange;          Tip montaj: Flush mounting; Panel mounting;          Tip contact (pluggable connector): Conector mama/priza;          Connector (connection type): for PCBs;          Mismatching protection: No;          Mating direction to the PCB: 0; °          PCB contact: THT;          Solder pin arrangement: over the entire female connector, in line;          Number of solder pins per potential: 1;          Culoare: orange;          Material group: I;          Material izolator: Polyamide 66 (PA 66);          Flammability class per UL94: V0;          Contact material: Copper alloy;          Contact plating: tin-plated;          Fire load: 0,171; MJ          Greutate: 9,6; g          Temperatura lucru: -60 ... +85 °C;          Product Group: 3 (Multi Conn. System);          Tip ambalare: BOX;          Tara de origine: DE;          GTIN: 4044918625579;          Customs tariff number: 85366990990;          Pret: 27,76 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-angled-spacer-flange-pin-spacing-5-08-mm-10-pole-orange-137901">https://www.materialelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-angled-spacer-flange-pin-spacing-5-08-mm-10-pole-orange-137901</a></p>
---	--