

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; SOCKET/OPEN-  
ENDED; 3-POLE; COD. B; H05VV-F 3 X 1.0 MM<sup>2</sup>; 5 M; 1.00 MM<sup>2</sup>;  
GRAY**

Note on Contact Resistance: approx. 1 m $\Omega$ ; of contact resistance $\hat{c}$  approx. 0.25 m $\Omega$ ;  
contact transition plug/socket;  
Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Curent nominal: 10; A  
Legend (ratings): (III / 3)  $\hat{a}$ %<sup>TM</sup> Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL 1977: 600; V  
Curent nominal UL 1977: 23; A  
Strip length: 9 mm / 0.35 inch;  
Numar poli: 3;  
Total number of potentials: 3;  
Conductor preparation: tip-bonded;  
Sheathed cable diameter: 6,3 ... 8 mm;  
Sectiunea transversala a firului: 1; mm<sup>2</sup>  
Strip length (outer insulation): 55; mm  
Connection type: Socket - Free end;  
Distanta intre pini: 10 mm / 0.394 inch;  
Total length: 5; m  
Coding: B;  
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);  
Retention force of a plug-in connection: when locked: > 80N;  
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending  
on pole number);  
Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25  
A), tested (4 mm<sup>2</sup>);  
Connection type: Socket - free end;  
Type of pre-assembled cable: Connecting cable;  
Cable type: Control line 3 x 1;  
Marking: 1 2 3;  
Protection type: IP20;  
Note on protection type: Only when mated (these compact connectors are not designed  
for use in open, easily accessible areas).;  
Potential marking: 1 2 3;  
Mismating protection: Yes;  
Locking of plug-in connection: locking lever;  
Locking lever: retrofittable;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire class per EN 50575: Eca;  
Contact material: Copper or copper alloy (surface-treated);  
Connector Culoare: gray;  
Printing color of mating face: black;  
Strain relief Culoare: black;  
Printing color of strain relief: white;  
Sheathed cable Culoare: gray;  
Printing color of sheathed cable: black;  
Sheath material: PVC;  
Greutate: 375,4; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: PVC cable for temperatures  $\leq$  70 °C  
(including halogen-free) Insulating parts for temperatures  $\leq$  105 °C;  
Tip ambalare: not packed;  
Tara de origine: DE;  
GTIN: 4055143507684;  
Customs tariff number: 85444290900;  
Pret: 47,43 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-socket-open-ended-3-pole-cod-b-h05vv-f-3-x-1-0-mm2-5-m-1-00-mm2-gray-137978>