

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO THT FEMALE HEADER; 0.6 X 1.0 MM SOLDER PIN; STRAIGHT; CLAMPING COLLAR; PIN SPACING 5.08 MM; 13-POLE; ORANGE</b></p> <p>Ratings per: IEC/EN 60664-1;          Tensiune nominala (III/3): 320; V          Tensiune nominala de supratensiune (III/3): 4; kV          Tensiune nominala (III/2): 320; V          Tensiune nominala de supratensiune (III/2): 4; kV          Tensiune nominala (II/2): 630; V          Tensiune nominala de supratensiune (II/2): 4; kV          Curent nominal: 12; A          Legend (ratings): (III / 2) <math>\hat{=}</math> Overvoltage category III / Pollution degree 2;          Tensiune nominala UL (Use Group B): 300; V          Curent nominal UL (Use Group B): 15; A          Tensiune nominala UL (Use Group D): 300; V          Curent nominal UL (Use Group D): 10; A          Certificari: UL 1059;          Tensiune nominala UL 1977: 600; V          Curent nominal UL 1977: 15; A          Tensiune nominala CSA (Use Group B): 300; V          Curent nominal CSA (Use Group B): 15; A          Tensiune nominala CSA (Use Group D): 300; V          Curent nominal CSA (Use Group D): 10; A          Numar poli: 13;          Numar total de conexiuni: 13;          Total number of potentials: 13;          Numar tipuri de conexiuni: 1;          Numar nivele: 1;          Distanta intre pini: 5.08 mm / 0.2 inch;          Latime: 80.84 mm / 3.183 inch;          Inaltime: 23.25 mm / 0.915 inch;          Inaltime de la fata: 18.25 mm / 0.719 inch;          Adancime: 11.6 mm / 0.457 inch;          Lungimea pinului de contact: 5; mm          Solder pin dimensions: 0.6 x 1 mm;          Diametrul de gaurire cu toleranta: 1.3 (+0.1) mm;          Tip montaj: Mounting flange;          Tip montaj: Feed-through mounting; Panel mounting;          Tip contact (pluggable connector): Conector mama/priza;          Connector (connection type): for PCBs;          Mismatching protection: No;          Mating direction to the PCB: 90; °          PCB contact: THT;          Solder pin arrangement: over the entire female connector, in line;          Number of solder pins per potential: 1;          Culoare: orange;          Material group: I;          Material izolator: Polyamide 66 (PA 66);          Flammability class per UL94: V0;          Contact material: Copper alloy;          Contact plating: tin-plated;          Greutate: 11,9; g          Temperatura lucru: -60 ... +85 °C;          Tip ambalare: BOX;          Tara de origine: DE;          GTIN: 4055143577625;          Customs tariff number: 85366990990;          Pret: 35,34 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-straight-clamping-collar-pin-spacing-5-08-mm-13-pole-orange-138189">https://www.materialelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-straight-clamping-collar-pin-spacing-5-08-mm-13-pole-orange-138189</a></p>
--	--