

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO 1-CONDUCTOR FEMALE PLUG; CLAMPING COLLAR; 2.5 MM<sup>2</sup>; PIN SPACING 7.62 MM; 10-POLE; 2,50 MM<sup>2</sup>; ORANGE</b></p> <p>Ratings per: IEC/EN 60664-1;                  Tensiune nominala (III/3): 500; V                  Tensiune nominala de supratensiune (III/3): 6; kV                  Tensiune nominala (III/2): 630; V                  Tensiune nominala de supratensiune (III/2): 6; kV                  Tensiune nominala (II/2): 1000; V                  Tensiune nominala de supratensiune (II/2): 6; kV                  Curent nominal: 16; A                  Legend (ratings): (III / 2) <math>\hat{a}</math>%™ Overvoltage category III / Pollution degree 2;                  Tensiune nominala UL (Use Group B): 300; V                  Curent nominal UL (Use Group B): 15; A                  Tensiune nominala UL (Use Group D): 300; V                  Curent nominal UL (Use Group D): 10; A                  Certificari: UL 1059;                  Tensiune nominala UL 1977: 600; V                  Curent nominal UL 1977: 15; A                  Tensiune nominala CSA (Use Group B): 300; V                  Curent nominal CSA (Use Group B): 15; A                  Tensiune nominala CSA (Use Group D): 300; V                  Curent nominal CSA (Use Group D): 10; A                  Tehnologie conexiune: CAGE CLAMP®;                  Tip actionare: Operating tool;                  Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;                  Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;                  Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;                  Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm<sup>2</sup>;                  Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;                  Numar poli: 10;                  Numar total de conexiuni: 10;                  Total number of potentials: 10;                  Numar tipuri de conexiuni: 1;                  Numar nivele: 1;                  Conductor entry direction to mating direction: 0; °                  Distanta intre pini: 7.62 mm / 0.3 inch;                  Latime: 88.46 mm / 3.483 inch;                  Inaltime: 14.3 mm / 0.563 inch;                  Adancime: 26.45 mm / 1.041 inch;                  Tip montaj: Mounting flange;                  Tip montaj: Feed-through mounting; Panel mounting;                  with reinforcing strips: 1;                  Tip contact (pluggable connector): Conector mama/priza;                  Connector (connection type): for conductors;                  Mismatching protection: No;                  Culoare: orange;                  Material group: I;                  Material izolator: Polyamide 66 (PA 66);                  Flammability class per UL94: V0;                  Clamping spring material: Chrome nickel spring steel (CrNi);                  Contact material: Copper alloy;                  Contact plating: tin-plated;                  Fire load: 0,383; MJ                  Greutate: 22,2; g                  Temperatura lucru: -60 ... +85 °C;                  Product Group: 3 (Multi Conn. System);                  Tip ambalare: BOX;                  Tara de origine: DE;                  GTIN: 4044918376785;                  Customs tariff number: 85366990990;                  Pret: 45,82 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/1-conductor-female-plug-clamping-collar-2-5-mm2-pin-spacing-7-62-mm-10-pole-2-50-mm2-orange-138473">https://www.materialelectrice.ro/1-conductor-female-plug-clamping-collar-2-5-mm2-pin-spacing-7-62-mm-10-pole-2-50-mm2-orange-138473</a></p>
--	---