

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO THT MALE HEADER; 1.2 X 1.2 MM SOLDER PIN; ANGLED; PIN SPACING 5.08 MM; 17-POLE; ORANGE</b></p> <p>Ratings per: IEC/EN 60664-1;                  Tensiune nominala (III/3): 250; V                  Tensiune nominala de supratensiune (III/3): 4; kV                  Tensiune nominala (III/2): 320; V                  Tensiune nominala de supratensiune (III/2): 4; kV                  Tensiune nominala (II/2): 630; V                  Tensiune nominala de supratensiune (II/2): 4; kV                  Curent nominal: 16; A                  Legend (ratings): (III / 2) <math>\hat{a}\%</math>™ Overvoltage category III / Pollution degree 2;                  Tensiune nominala UL (Use Group B): 300; V                  Curent nominal UL (Use Group B): 15; A                  Tensiune nominala UL (Use Group D): 300; V                  Curent nominal UL (Use Group D): 10; A                  Certificari: UL 1059;                  Tensiune nominala UL 1977: 600; V                  Curent nominal UL 1977: 15; A                  Tensiune nominala CSA (Use Group B): 300; V                  Curent nominal CSA (Use Group B): 15; A                  Tensiune nominala CSA (Use Group D): 300; V                  Curent nominal CSA (Use Group D): 10; A                  Numar poli: 17;                  Total number of potentials: 17;                  Numar tipuri de conexiuni: 1;                  Numar nivele: 1;                  Distanta intre pini: 5.08 mm / 0.2 inch;                  Latime: 89.48 mm / 3.523 inch;                  Inaltime: 12.2 mm / 0.48 inch;                  Inaltime de la fata: 8.4 mm / 0.331 inch;                  Adancime: 12 mm / 0.472 inch;                  Lungimea pinului de contact: 3,8; mm                  Solder pin dimensions: 1.2 x 1.2 mm;                  Diametrul de gaurire cu toleranta: 1.7 (+0.1) mm;                  Tip contact (pluggable connector): Conector tata/fisa;                  Connector (connection type): for PCBs;                  Mismatching protection: No;                  Mating direction to the PCB: 0; °                  PCB contact: THT;                  Solder pin arrangement: over the entire male connector, in line;                  Number of solder pins per potential: 1;                  Culoare: orange;                  Material group: I;                  Material izolator: Polyamide 66 (PA 66);                  Flammability class per UL94: V0;                  Contact material: Cupru electrolitic(ECu);                  Contact plating: tin-plated;                  Fire load: 0,098; MJ                  Greutate: 6,5; g                  Temperatura lucru: -60 ... +100 °C;                  Product Group: 3 (Multi Conn. System);                  Tip ambalare: BOX;                  Tara de origine: PL;                  GTIN: 4044918931472;                  Customs tariff number: 85366990990;                  Pret: 24,31 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/tht-male-header-1-2-x-1-2-mm-solder-pin-angled-pin-spacing-5-08-mm-17-pole-orange-138590">https://www.materialelectrice.ro/tht-male-header-1-2-x-1-2-mm-solder-pin-angled-pin-spacing-5-08-mm-17-pole-orange-138590</a></p>
--	--